



System Fact Sheet

SYSTEM

Introduced: February 1993
Discontinued: October 1993
Gestalt ID: 52
Form Factor: Centris 610
Weight (lbs.): 14
Dimensions (inches): 3.4 H x 16.3 W x 15.6 D

POWER

Max. Watts: 86
Amps: 1.70
BTU Per Hour: 294.12
Voltage Range: 100-240
Freq'y Range (Hz): 47-63
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 2
Video: DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: none
Ethernet: opt. AAUI-15
Microphone Port Type: Omni
 Printer
 Modem
 Speaker
 Headphone
 Remote Control

VIDEO **Built-in Display:** none

VRAM Speed: 100 ns
VRAM Needed: built in
 2x256K

Video Configuration: 512K VRAM
 1MB VRAM

	512	640	640	640	800	832	1024	1152	1280
	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
	16	n/a	8	4	8	8	4	4	n/a
	16	n/a	16	8	16	16	8	8	n/a

Maximum Color Bit-depth¹ At:

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGIC BOARD

Main Processor: 68LC040, 40 MHz
PMMU: integrated
FPU: none
Data Path: 32-bit, 20 MHz
L1 Cache: 8K
L2 Cache: none
Secondary Processor: none
Slots: one 7" NuBus or PDS

MEMORY

Memory on Logic Board: 4MB
Minimum RAM: 4MB
Maximum RAM: 68MB
RAM Slots: 2 72-pin
Minimum RAM Speed: 80 ns
RAM Sizes: 4, 8, 16, 32MB
Install in Groups of: 1

SOFTWARE **Speech Recognition Supported**

Addressing Modes: 24-, 32-bit
Original SSW: 7.1
Original Enabler: System Enabler 040 v1.0

ROM ID: \$067C
ROM Version: n/a
ROM Size: 1MB
AppleTalk Version: 57.0.4

Supported Macintosh System Software:

<input type="checkbox"/> <1.0	<input type="checkbox"/> 6.0	<input type="checkbox"/> 6.0.8	<input type="checkbox"/> 7.1P2	<input type="checkbox"/> 7.1.2
<input type="checkbox"/> 1.0	<input type="checkbox"/> 6.0.1	<input type="checkbox"/> 7.0	<input type="checkbox"/> 7.1P3	<input checked="" type="checkbox"/> 7.5
<input type="checkbox"/> 1.1	<input type="checkbox"/> 6.0.2	<input type="checkbox"/> 7.0.1	<input type="checkbox"/> 7.1P5	<input checked="" type="checkbox"/> 7.5.1
<input type="checkbox"/> 2.0	<input type="checkbox"/> 6.0.3	<input type="checkbox"/> 7.0.1P	<input type="checkbox"/> 7.1P6	<input type="checkbox"/> 7.5.2
<input type="checkbox"/> 2.0.1	<input type="checkbox"/> 6.0.4	<input checked="" type="checkbox"/> 7.1	<input checked="" type="checkbox"/> 7.1.1 (Pro)	<input checked="" type="checkbox"/> 7.5.3
<input type="checkbox"/> 5.0	<input type="checkbox"/> 6.0.5	<input type="checkbox"/> 7.1P	<input type="checkbox"/> 7.1.1	<input checked="" type="checkbox"/> 7.5.5
<input type="checkbox"/> 5.1	<input type="checkbox"/> 6.0.7	<input type="checkbox"/> 7.1P1	<input type="checkbox"/> 7.1.2	<input checked="" type="checkbox"/> 7.6

SOUND

Built-in Microphone

Microphone Port Type: Omni
Sound In: mono, 8-bit
Sound Out: stereo, 8-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: auto
Internal HD Size: 80-500MB
Internal HD Interface: SCSI
Original CD-ROM Speed: 2x

Note: n/a = information not available or not applicable