



### System Fact Sheet

#### SYSTEM

**Introduced:** February 1993  
**Discontinued:** February 1994  
**Gestalt ID:** 27  
**Form Factor:** LC  
**Weight (lbs.):** 8.8  
**Dimensions (inches):** 2.9 H x 12.2 W x 15.3 D

#### POWER

**Max. Watts:** 50  
**Amps:** 0.42  
**BTU Per Hour:** 171  
**Voltage Range:** 100-240  
**Freq'y Range (Hz):** 47-63  
**Battery Type:** 3.6V lithium  
 **Soft Power**  
 **Monitor Power Outlet**

#### PORTS

**ADB:** 1  
**Video:** DB-15  
**Floppy:** none  
**SCSI:** DB-25  
**GeoPort Connectors:** none  
**Ethernet:** none  
**Microphone Port Type:** Omni  
 **Printer**  
 **Modem**  
 **Speaker**  
 **Headphone**  
 **Remote Control**

#### VIDEO

**Built-in Display:** none

#### Maximum Color Bit-depth<sup>1</sup> At:

VRAM Speed:	VRAM Needed:	Video Configuration:	512 x384	640 x400	640 x480	640 x870 <sup>2</sup>	800 x600	832 x624	1024 x768	1152 x870	1280 x1024
100 ns	built in	512K VRAM	16	16	8	4	n/a	8	n/a	n/a	n/a
	1x256K	768K VRAM	16	16	16	8	n/a	16	n/a	n/a	n/a

<sup>1</sup> 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

<sup>2</sup> The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

512K VRAM SIMMs may be installed, but only 256K of each SIMM will be used.

#### LOGIC BOARD

**Main Processor:** 68030, 25 MHz  
**PMMU:** integrated  
**FPU:** opt. 68882  
**Data Path:** 32-bit, 25 MHz  
**L1 Cache:** 0.5K  
**L2 Cache:** none  
**Secondary Processor:** none  
**Slots:** 1 LC III PDS

#### MEMORY

**Memory on Logic Board:** 4MB  
**Minimum RAM:** 4MB  
**Maximum RAM:** 36MB  
**RAM Slots:** 1 72-pin  
**Minimum RAM Speed:** 80 ns  
**RAM Sizes:** 1, 2, 4, 8, 16, 32MB  
**Install in Groups of:** 1

#### SOFTWARE

**Speech Recognition Supported**

**Addressing Modes:** 24-, 32-bit  
**Original SSW:** 7.1  
**Original Enabler:** System Enabler 003

**ROM ID:** \$067C  
**ROM Version:** \$22  
**ROM Size:** 1MB  
**AppleTalk Version:** 57.0.4

#### Supported Macintosh System Software:

<1.0    6.0    6.0.8    7.1P2    7.1.2  
 1.0    6.0.1    7.0    7.1P3    7.5  
 1.1    6.0.2    7.0.1    7.1P5    7.5.1  
 2.0    6.0.3    7.0.1P    7.1P6    7.5.2  
 2.0.1    6.0.4    7.1    7.1.1 (Pro)    7.5.3  
 5.0    6.0.5    7.1P    7.1.1    7.5.5  
 5.1    6.0.7    7.1P1    7.1.2    7.6

#### SOUND

**Microphone Port Type:** Omni  
**Sound In:** mono, 8-bit  
**Sound Out:** mono, 8-bit

**Built-in Microphone**

#### STORAGE

**Supports  
Internal  
CD-ROM**

**Floppy Size:** 1.44MB  
**Floppy Inject:** auto  
**Internal HD Size:** 80-160MB  
**Internal HD Interface:** SCSI  
**Original CD-ROM Speed:** n/a