



System Fact Sheet

SYSTEM

Introduced: October 1993
Discontinued: October 1994
Gestalt ID: 94
Form Factor: LC
Weight (lbs.): 8.8
Dimensions (inches): 2.9 H x 12.2 W x 15.3 D

POWER

Max. Watts: 30
Amps: 0.44
BTU Per Hour: 102.6
Voltage Range: 100-240
Freq'y Range (Hz): 47-63
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: none
Ethernet: none
Microphone Port Type: PlainTalk

Printer **Speaker**
 Modem **Headphone**
 Remote Control

VIDEO **Built-in Display:** none

Maximum Color Bit-depth¹ At:

| | | | | | | | | | | | |
|--------------------|---------------------|-----------------------------|------|------|------|-------------------|------|------|------|------|-------|
| | | | 512 | 640 | 640 | 640 | 800 | 832 | 1024 | 1152 | 1280 |
| VRAM Speed: | VRAM Needed: | Video Configuration: | x384 | x400 | x480 | x870 ² | x600 | x624 | x768 | x870 | x1024 |
| 80 ns | 2x256K | 512K VRAM | 16 | n/a | 8 | 4 | n/a | 8 | 4 | 4 | n/a |
| | 2x512K | 1MB VRAM | 16 | n/a | 16 | 8 | n/a | 16 | 8 | 8 | n/a |

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGIC BOARD

Main Processor: 68LC040, 50 MHz
PMMU: integrated
FPU: none
Data Path: 32-bit, 25 MHz
L1 Cache: 8K
L2 Cache: none
Secondary Processor: none
Slots: 1 LC III PDS

MEMORY

Memory on Logic Board: 4MB
Minimum RAM: 4MB
Maximum RAM: 36MB
RAM Slots: 1 72-pin
Minimum RAM Speed: 80 ns
RAM Sizes: 1, 2, 4, 8, 16, 32MB
Install in Groups of: 1

SOFTWARE **Speech Recognition Supported**

Addressing Modes: 24-, 32-bit
Original SSW: 7.1
Original Enabler: System Enabler 065

ROM ID: \$067C
ROM Version: n/a
ROM Size: 512k*
AppleTalk Version: 57.0.4

Supported Macintosh System Software:

| | | | | |
|--------------------------------|--------------------------------|---|---|---|
| <input type="checkbox"/> <1.0 | <input type="checkbox"/> 6.0 | <input type="checkbox"/> 6.0.8 | <input type="checkbox"/> 7.1P2 | <input type="checkbox"/> 7.1.2 |
| <input type="checkbox"/> 1.0 | <input type="checkbox"/> 6.0.1 | <input type="checkbox"/> 7.0 | <input type="checkbox"/> 7.1P3 | <input checked="" type="checkbox"/> 7.5 |
| <input type="checkbox"/> 1.1 | <input type="checkbox"/> 6.0.2 | <input type="checkbox"/> 7.0.1 | <input type="checkbox"/> 7.1P5 | <input checked="" type="checkbox"/> 7.5.1 |
| <input type="checkbox"/> 2.0 | <input type="checkbox"/> 6.0.3 | <input type="checkbox"/> 7.0.1P | <input type="checkbox"/> 7.1P6 | <input type="checkbox"/> 7.5.2 |
| <input type="checkbox"/> 2.0.1 | <input type="checkbox"/> 6.0.4 | <input checked="" type="checkbox"/> 7.1 | <input checked="" type="checkbox"/> 7.1.1 (Pro) | <input checked="" type="checkbox"/> 7.5.3 |
| <input type="checkbox"/> 5.0 | <input type="checkbox"/> 6.0.5 | <input type="checkbox"/> 7.1P | <input type="checkbox"/> 7.1.1 | <input checked="" type="checkbox"/> 7.5.5 |
| <input type="checkbox"/> 5.1 | <input type="checkbox"/> 6.0.7 | <input type="checkbox"/> 7.1P1 | <input type="checkbox"/> 7.1.2 | <input checked="" type="checkbox"/> 7.6 |

ROM = 512k: expandable to 1MB

SOUND

Built-in Microphone

Microphone Port Type: PlainTalk
Sound In: mono, 8-bit
Sound Out: stereo, 8-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 80-160MB
Internal HD Interface: SCSI
Original CD-ROM Speed: n/a

Note: n/a = information not available or not applicable