



System Fact Sheet

SYSTEM

Introduced: February 1993
Discontinued: May 1994
Gestalt ID: 49
Form Factor: Color Classic
Weight (lbs.): 22.5
Dimensions (inches): 14.5 H x 9.9 W x 12.6 D

POWER

Max. Watts: 100
Amps: 0.83
BTU Per Hour: 342
Voltage Range: 90-240
Freq'y Range (Hz): 47-63
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 2
Video: none
Floppy: none
SCSI: DB-25
GeoPort Connectors: none
Ethernet: none
Microphone Port Type: Omni

Printer **Speaker**
 Modem **Headphone**
 Remote Control

VIDEO **Built-in Display:** 10" Sony Trinitron RGB

			<i>Maximum Color Bit-depth¹ At:</i>								
			512	640	640	640	800	832	1024	1152	1280
VRAM Speed:	VRAM Needed:	Video Configuration:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
100 ns	built in	256K VRAM	8	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	1x256K	512K VRAM	16	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGIC BOARD

Main Processor: 68030, 16 MHz
PMMU: integrated
FPU: opt. 68882
Data Path: 16-bit, 16 MHz
L1 Cache: 0.5K
L2 Cache: none
Secondary Processor: none
Slots: 1 LC PDS

MEMORY

Memory on Logic Board: 4MB
Minimum RAM: 4MB
Maximum RAM: 10MB
RAM Slots: 2 30-pin
Minimum RAM Speed: 100 ns
RAM Sizes: 1, 2, 4MB
Install in Groups of: 2

When all SIMM slots are filled with 4MB SIMMs, the lower 2MB of RAM on the logic board cannot be addressed.

SOFTWARE **Speech Recognition Supported**

Addressing Modes: 24-, 32-bit
Original SSW: 7.1
Original Enabler: System Enabler 401

ROM ID: \$067C
ROM Version: \$24
ROM Size: 1MB
AppleTalk Version: 57.0.4

Supported Macintosh System Software:

<input type="checkbox"/> <1.0	<input type="checkbox"/> 6.0	<input type="checkbox"/> 6.0.8	<input type="checkbox"/> 7.1P2	<input type="checkbox"/> 7.1.2
<input type="checkbox"/> 1.0	<input type="checkbox"/> 6.0.1	<input type="checkbox"/> 7.0	<input type="checkbox"/> 7.1P3	<input checked="" type="checkbox"/> 7.5
<input type="checkbox"/> 1.1	<input type="checkbox"/> 6.0.2	<input type="checkbox"/> 7.0.1	<input type="checkbox"/> 7.1P5	<input checked="" type="checkbox"/> 7.5.1
<input type="checkbox"/> 2.0	<input type="checkbox"/> 6.0.3	<input type="checkbox"/> 7.0.1P	<input type="checkbox"/> 7.1P6	<input type="checkbox"/> 7.5.2
<input type="checkbox"/> 2.0.1	<input type="checkbox"/> 6.0.4	<input checked="" type="checkbox"/> 7.1	<input checked="" type="checkbox"/> 7.1.1 (Pro)	<input checked="" type="checkbox"/> 7.5.3
<input type="checkbox"/> 5.0	<input type="checkbox"/> 6.0.5	<input type="checkbox"/> 7.1P	<input type="checkbox"/> 7.1.1	<input checked="" type="checkbox"/> 7.5.5
<input type="checkbox"/> 5.1	<input type="checkbox"/> 6.0.7	<input type="checkbox"/> 7.1P1	<input type="checkbox"/> 7.1.2	<input checked="" type="checkbox"/> 7.6

SOUND

Built-in Microphone

Microphone Port Type: Omni
Sound In: mono, 8-bit
Sound Out: mono, 8-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: auto
Internal HD Size: 40-160MB
Internal HD Interface: SCSI
Original CD-ROM Speed: n/a