



System Fact Sheet

SYSTEM

Introduced: March 1987
Discontinued: August 1989
Gestalt ID: 5
Form Factor: SE
Weight (lbs.): 17
Dimensions (inches): 13.6 H x 9.69 W x 10.9 D

Some systems shipped with two 800K floppy disk drives.

POWER

Max. Watts: 100
Amps: 0.83
BTU Per Hour: 342
Voltage Range: 90-270
Freq'y Range (Hz): 47-63
Battery Type: n/a
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 2
Video: none
Floppy: DB-19
SCSI: DB-25
GeoPort Connectors: none
Ethernet: none
Microphone Port Type: none
 Printer
 Modem
 Speaker
 Headphone
 Remote Control

VIDEO

Built-in Display: 9" monochrome CRT

Maximum Color Bit-depth¹ At:

VRAM Speed:	VRAM Needed:	Video Configuration:	512	640	640	640	800	832	1024	1152	1280
n/a	built in	built-in CRT	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
			1	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

Screen size is 512x342.

LOGIC BOARD

Main Processor: 68000, 8 MHz
PMMU: none
FPU: none
Data Path: 16-bit, 8 MHz
L1 Cache: none
L2 Cache: none
Secondary Processor: none
Slots: 1 SE PDS

MEMORY

Memory on Logic Board: none
Minimum RAM: 1MB
Maximum RAM: 4MB
RAM Slots: 4 30-pin
Minimum RAM Speed: 150 ns
RAM Sizes: 256K, 1MB
Install in Groups of: 2

This system cannot use two-chip 1MB SIMMs.

SOFTWARE

Speech Recognition Supported

Addressing Modes: 24-bit
Original SSW: 2.0
Original Enabler: none

ROM ID: \$0276
ROM Version: 0
ROM Size: 256K
AppleTalk Version: 48

Supported Macintosh System Software:

<input type="checkbox"/> <1.0	<input checked="" type="checkbox"/> 6.0	<input checked="" type="checkbox"/> 6.0.8	<input type="checkbox"/> 7.1P2	<input type="checkbox"/> 7.1.2
<input type="checkbox"/> 1.0	<input checked="" type="checkbox"/> 6.0.1	<input checked="" type="checkbox"/> 7.0	<input type="checkbox"/> 7.1P3	<input checked="" type="checkbox"/> 7.5
<input type="checkbox"/> 1.1	<input checked="" type="checkbox"/> 6.0.2	<input checked="" type="checkbox"/> 7.0.1	<input type="checkbox"/> 7.1P5	<input checked="" type="checkbox"/> 7.5.1
<input checked="" type="checkbox"/> 2.0	<input checked="" type="checkbox"/> 6.0.3	<input type="checkbox"/> 7.0.1P	<input type="checkbox"/> 7.1P6	<input type="checkbox"/> 7.5.2
<input checked="" type="checkbox"/> 2.0.1	<input checked="" type="checkbox"/> 6.0.4	<input checked="" type="checkbox"/> 7.1	<input checked="" type="checkbox"/> 7.1.1 (Pro)	<input checked="" type="checkbox"/> 7.5.3
<input checked="" type="checkbox"/> 5.0	<input checked="" type="checkbox"/> 6.0.5	<input type="checkbox"/> 7.1P	<input type="checkbox"/> 7.1.1	<input checked="" type="checkbox"/> 7.5.5
<input checked="" type="checkbox"/> 5.1	<input checked="" type="checkbox"/> 6.0.7	<input type="checkbox"/> 7.1P1	<input type="checkbox"/> 7.1.2	<input type="checkbox"/> 7.6

SOUND

Microphone Port Type: none
Sound In: none
Sound Out: mono, 8-bit

Built-in Microphone

STORAGE

Supports Internal CD-ROM

Floppy Size: 800K
Floppy Inject: auto
Internal HD Size: none-40MB
Internal HD Interface: SCSI
Original CD-ROM Speed: n/a