



System Fact Sheet

SYSTEM

Introduced: May 1998
Discontinued: n/a
Gestalt ID: 314
Form Factor: PowerBook G3 Series
Weight (lbs.): 7.2
Dimensions (inches): 2 H x 12.7 W x 10.4 D

*Family Model #M4753
 Weight includes modem, battery and
 CD-ROM module*

POWER

Max. Watts: 45
Amps: 1.2
BTU Per Hour: 153.9
Voltage Range: 100-240
Freq'y Range (Hz): 50-60
Battery Type: 49 Wh Lithium Ion
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: HDI-15
Floppy: none
SCSI: HDI-30
GeoPort Connectors: 1
Ethernet: 10Base-T
Microphone Port Type: PlainTalk
 Printer
 Modem
 Speaker
 Headphone
 Remote Control

*24-bit video output port
 SCSI port for connecting up to 7 devices*

VIDEO

Built-in Display: 12.1" (diagonal) SVGA STN passive-matrix

Maximum Color Bit-depth¹ At:

	512	640	640	640	800	832	1024	1152	1280
VRAM Speed:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
VRAM Needed:	n/a	built-in							
Video Configuration:	n/a	n/a	n/a	n/a	16	n/a	n/a	n/a	n/a

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGIC BOARD

Main Processor: G3, 233
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 66 MHz
L1 Cache: 64kb
L2 Cache: none
Secondary Processor: none
Slots: 2 Type II PC Card (1Type III)

Slots : 2 Type II PC Card s or 1 Type III PC Card or CardBus cards

MEMORY

Memory on Logic Board: none
Minimum RAM: 32MB
Maximum RAM: 192MB
RAM Slots: 2 144pin
Minimum RAM Speed: 100 MHz
RAM Sizes: 32MB, 64MB, 128MB
Install in Groups of: 1

*144 -pin SDRAM
 2 SO-DIMM slots supports up to 192MB
 128 MB DIMM installs in top slot only*

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 8.1
Original Enabler: PowerBook G3 Series

ROM ID: n/a
ROM Version: n/a
ROM Size: 4MB
AppleTalk Version: n/a

Supported Macintosh System Software:

- <1.0 6.0 6.0.8 7.1P2 7.1.2
- 1.0 6.0.1 7.0 7.1P3 7.5
- 1.1 6.0.2 7.0.1 7.1P5 7.5.1
- 2.0 6.0.3 7.0.1P 7.1P6 7.5.2
- 2.0.1 6.0.4 7.1 7.1.1 (Pro) 7.5.3
- 5.0 6.0.5 7.1P 7.1.1 7.5.5
- 5.1 6.0.7 7.1P1 7.1.2 7.6

SOUND

Built-in Microphone

Microphone Port Type: PlainTalk
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

STORAGE

**Supports
 Internal
 CD-ROM**

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 2MB
Internal HD Interface: IDE
Original CD-ROM Speed: 20x

*DVD -ROM drive available
 CD-ROM and Floppy are removable modules*