



### System Fact Sheet

#### SYSTEM

**Introduced:** November 1996  
**Discontinued:** n/a  
**Gestalt ID:** 514  
**Form Factor:** PM 4400  
**Weight (lbs.):** 24  
**Dimensions (inches):** 5.43 H x 15.12 W x 17.37 D

*This system is not sold in the U.S.*

#### POWER

**Max. Watts:** 150  
**Amps:** 3.00  
**BTU Per Hour:** 513  
**Voltage Range:** 110/220  
**Freq'y Range (Hz):** 47-63  
**Battery Type:** 4.5V alkaline  
 **Soft Power**  
 **Monitor Power Outlet**

#### PORTS

**ADB:** 1  
**Video:** DB-15  
**Floppy:** none  
**SCSI:** DB-25  
**GeoPort Connectors:** 2  
**Ethernet:** none  
**Microphone Port Type:** PlainTalk  
 **Printer**  
 **Modem**  
 **Speaker**  
 **Headphone**  
 **Remote Control**

#### VIDEO

**Built-in Display:** none

#### Maximum Color Bit-depth<sup>1</sup> At:

VRAM Speed:	VRAM Needed:	Video Configuration:	512	640	640	640	800	832	1024	1152	1280
			x384	x400	x480	x870 <sup>2</sup>	x600	x624	x768	x870	x1024
n/a	1x1MB	1MB DRAM	16	n/a	16	8	16	16	8	8	n/a
	1x2MB	2MB DRAM	24	n/a	24	8	24	24	16	16	8
	1x4MB	4MB DRAM	24	n/a	24	8	24	24	24	16	16

<sup>1</sup> 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

<sup>2</sup> The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

*Can use EDO DRAM, SGRAM, or SDRAM for video expansion.*

#### LOGIC BOARD

**Main Processor:** 603e, 160 MHz  
**PMMU:** integrated  
**FPU:** integrated  
**Data Path:** 64-bit, 40 MHz  
**L1 Cache:** 32K  
**L2 Cache:** opt'l.  
**Secondary Processor:** none  
**Slots:** 3 PCI

*Supports one 7-inch and two 12-inch PCI slots.*

#### MEMORY

**Memory on Logic Board:** none  
**Minimum RAM:** 16MB  
**Maximum RAM:** 96MB  
**RAM Slots:** 3 168-pin  
**Minimum RAM Speed:** 60 ns  
**RAM Sizes:** 8, 16, 32MB  
**Install in Groups of:** 1

*Uses JEDEC-standard 3.3-volt unbuffered EDO DIMM devices. DRAM slot 1 supports only single-bank DIMMs.*

#### SOFTWARE

**Speech Recognition Supported**

**Addressing Modes:** 32-bit  
**Original SSW:** 7.5.3  
**Original Enabler:** System Enabler 827

**ROM ID:** \$077D  
**ROM Version:** \$37  
**ROM Size:** 4MB  
**AppleTalk Version:** 60.1.1

#### Supported Macintosh System Software:

<input type="checkbox"/> <1.0	<input type="checkbox"/> 6.0	<input type="checkbox"/> 6.0.8	<input type="checkbox"/> 7.1P2	<input type="checkbox"/> 7.1.2
<input type="checkbox"/> 1.0	<input type="checkbox"/> 6.0.1	<input type="checkbox"/> 7.0	<input type="checkbox"/> 7.1P3	<input type="checkbox"/> 7.5
<input type="checkbox"/> 1.1	<input type="checkbox"/> 6.0.2	<input type="checkbox"/> 7.0.1	<input type="checkbox"/> 7.1P5	<input type="checkbox"/> 7.5.1
<input type="checkbox"/> 2.0	<input type="checkbox"/> 6.0.3	<input type="checkbox"/> 7.0.1P	<input type="checkbox"/> 7.1P6	<input type="checkbox"/> 7.5.2
<input type="checkbox"/> 2.0.1	<input type="checkbox"/> 6.0.4	<input type="checkbox"/> 7.1	<input type="checkbox"/> 7.1.1 (Pro)	<input checked="" type="checkbox"/> 7.5.3
<input type="checkbox"/> 5.0	<input type="checkbox"/> 6.0.5	<input type="checkbox"/> 7.1P	<input type="checkbox"/> 7.1.1	<input type="checkbox"/> 7.5.5
<input type="checkbox"/> 5.1	<input type="checkbox"/> 6.0.7	<input type="checkbox"/> 7.1P1	<input type="checkbox"/> 7.1.2	<input checked="" type="checkbox"/> 7.6

#### SOUND

**Microphone Port Type:** PlainTalk  
 **Built-in Microphone**  
**Sound In:** stereo, 16-bit  
**Sound Out:** stereo, 16-bit

#### STORAGE

**Supports Internal CD-ROM**

**Floppy Size:** 1.44MB  
**Floppy Inject:** manual  
**Internal HD Size:** 1.2GB  
**Internal HD Interface:** ATA  
**Original CD-ROM Speed:** 8x