Apple
Spec Database

Power Macintosh 5200/75 LC

System Fact Sheet

System

Introduced: April 1995
Discontinued: April 1996
Gestalt ID: 41
Form Factor: PM 5200
Weight (lbs.): 47
Dimensions (inches): 17.5 H x 15.1 W x 16 D

Power

Max. Watts: 125
Amps: 4.00
BTU Per Hour: 427.5
Voltage Range: 110-240
Freq'y Range (Hz): 50-60
Battery Type: 4.5V alkaline
☒ **Soft Power**
☐ **Monitor Power Outlet**

Ports

ADB: 1
Video: opt. DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: none
Ethernet: none
Microphone Port Type: PlainTalk
☒ **Printer**
☒ **Modem**
☒ **Speaker**
☒ **Headphone**
☒ **Remote Control**

Video

Built-in Display: *15" shadow mask RGB*

VRAM Speed:	VRAM Needed:	Video Configuration:	Maximum Color Bit-depth[1] At: 512 x384	640 x400	640 x480	640 x870[2]	800 x600	832 x624	1024 x768	1152 x870	1280 x1024
60 ns	built in	1MB DRAM	n/a	n/a	16	n/a	8	8	n/a	n/a	n/a

[1] 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
[2] The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

Video in not supported at 832x624.

Logic Board

Main Processor: 603, 75 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 37.5 MHz
L1 Cache: 16K
L2 Cache: 256K
Secondary Processor: none
Slots: LC, comm, TV, video in/out

Memory

Memory on Logic Board: none
Minimum RAM: 8MB
Maximum RAM: 64MB
RAM Slots: 2 72-pin
Minimum RAM Speed: 80 ns
RAM Sizes: 4, 8, 16, 32MB
Install in Groups of: 1

Software

☒ **Speech Recognition Supported**

Addressing Modes: 32-bit
Original SSW: 7.5.1
Original Enabler: System Enabler 406

ROM ID: $077D
ROM Version: $26
ROM Size: 4MB
AppleTalk Version: 58.1.3

Supported Macintosh System Software:

☐ <1.0	☐ 6.0	☐ 6.0.8	☐ 7.1P2	☐ 7.1.2
☐ 1.0	☐ 6.0.1	☐ 7.0	☐ 7.1P3	☐ 7.5
☐ 1.1	☐ 6.0.2	☐ 7.0.1	☐ 7.1P5	☒ 7.5.1
☐ 2.0	☐ 6.0.3	☐ 7.0.1P	☐ 7.1P6	☐ 7.5.2
☐ 2.0.1	☐ 6.0.4	☐ 7.1	☐ 7.1.1 (Pro)	☒ 7.5.3
☐ 5.0	☐ 6.0.5	☐ 7.1P	☐ 7.1.1	☒ 7.5.5
☐ 5.1	☐ 6.0.7	☐ 7.1P1	☐ 7.1.2	☒ 7.6

Sound

☒ **Built-in Microphone**

Microphone Port Type: PlainTalk
Sound In: mono, 16-bit
Sound Out: stereo, 16-bit

Some systems have 8-bit sound. INPUT: impedance 100 kOhm; avg. line level 100 mV rms; avg. mic. level 70 mV rms, max. input level 1.8 V

Storage

☒ **Supports Internal CD-ROM**

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 500MB
Internal HD Interface: IDE
Original CD-ROM Speed: 2x

Note: n/a = information not available or not applicable