



System Fact Sheet

SYSTEM

Introduced: January 1995
Discontinued: April 1995
Gestalt ID: 100
Form Factor: Centris 610
Weight (lbs.): 14
Dimensions (inches): 3.4 H x 16.3 W x 15.6 D

POWER

Max. Watts: 210
Amps: 1.70
BTU Per Hour: 718.2
Voltage Range: 100-240
Freq'y Range (Hz): 50-60
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15, HDI-45
Floppy: none
SCSI: DB-25
GeoPort Connectors: 2
Ethernet: AAUI-15
Microphone Port Type: PlainTalk
 Printer Speaker
 Modem Headphone
 Remote Control

*Includes S-video ports for video in and out.
 RCA ports available via included adapter.*

VIDEO

Built-in Display: none

Maximum Color Bit-depth¹ At:

VRAM Speed:	VRAM Needed:	Video Configuration:	512 x384	640 x400	640 x480	640 x870 ²	800 x600	832 x624	1024 x768	1152 x870	1280 x1024
80 ns	built in	DRAM (HDI-45)	16	n/a	16	8	n/a	8	n/a	n/a	n/a
	built in	2MB VRAM	24	24	24	8	24	24	16	16	n/a

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGIC BOARD

Main Processor: 601, 66 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 33 MHz
L1 Cache: 32K
L2 Cache: 256K
Secondary Processor: none
Slots: PDS filled

MEMORY

Memory on Logic Board: 8MB
Minimum RAM: 8MB
Maximum RAM: 72MB
RAM Slots: 2 72-pin
Minimum RAM Speed: 80 ns
RAM Sizes: 4, 8, 16, 32MB
Install in Groups of: 2

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 7.5
Original Enabler: PowerPC Enabler v1.1.1

ROM ID: \$077D
ROM Version: \$20
ROM Size: 4MB
AppleTalk Version: n/a

Supported Macintosh System Software:

- | | | | | |
|--------------------------------|--------------------------------|---------------------------------|--------------------------------------|---|
| <input type="checkbox"/> <1.0 | <input type="checkbox"/> 6.0 | <input type="checkbox"/> 6.0.8 | <input type="checkbox"/> 7.1P2 | <input type="checkbox"/> 7.1.2 |
| <input type="checkbox"/> 1.0 | <input type="checkbox"/> 6.0.1 | <input type="checkbox"/> 7.0 | <input type="checkbox"/> 7.1P3 | <input checked="" type="checkbox"/> 7.5 |
| <input type="checkbox"/> 1.1 | <input type="checkbox"/> 6.0.2 | <input type="checkbox"/> 7.0.1 | <input type="checkbox"/> 7.1P5 | <input checked="" type="checkbox"/> 7.5.1 |
| <input type="checkbox"/> 2.0 | <input type="checkbox"/> 6.0.3 | <input type="checkbox"/> 7.0.1P | <input type="checkbox"/> 7.1P6 | <input type="checkbox"/> 7.5.2 |
| <input type="checkbox"/> 2.0.1 | <input type="checkbox"/> 6.0.4 | <input type="checkbox"/> 7.1 | <input type="checkbox"/> 7.1.1 (Pro) | <input checked="" type="checkbox"/> 7.5.3 |
| <input type="checkbox"/> 5.0 | <input type="checkbox"/> 6.0.5 | <input type="checkbox"/> 7.1P | <input type="checkbox"/> 7.1.1 | <input checked="" type="checkbox"/> 7.5.5 |
| <input type="checkbox"/> 5.1 | <input type="checkbox"/> 6.0.7 | <input type="checkbox"/> 7.1P1 | <input type="checkbox"/> 7.1.2 | <input checked="" type="checkbox"/> 7.6 |

SOUND

Microphone Port Type: PlainTalk
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

Built-in Microphone

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 350MB
Internal HD Interface: SCSI
Original CD-ROM Speed: 2x