



System Fact Sheet

SYSTEM

Introduced: October 1996
Discontinued: n/a
Gestalt ID: 58
Form Factor: Performa 6400
Weight (lbs.): 44.5
Dimensions (inches): 16 H x 7.8 W x 16.9 D

POWER

Max. Watts: 220
Amps: 3.00
BTU Per Hour: 752.4
Voltage Range: 100-125/200-240
Freq'y Range (Hz): 47-63
Battery Type: 4.5V alkaline
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: 2
Ethernet: none
Microphone Port Type: PlainTalk
 Printer
 Modem
 Speaker
 Headphone
 Remote Control

VIDEO

Built-in Display: none

Maximum Color Bit-depth¹ At:

VRAM Speed:	VRAM Needed:	Video Configuration:	512	640	640	640	800	832	1024	1152	1280
x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024			
60 ns	built in	1MB DRAM	n/a	n/a	16	n/a	16	8	8	n/a	n/a

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGIC BOARD

Main Processor: 603e, 200 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 40 MHz
L1 Cache: 32K
L2 Cache: 256K
Secondary Processor: opt. PC Compatibility Card
Slots: 2 PCI, Comm II, TV, video in

MEMORY

Memory on Logic Board: 8MB
Minimum RAM: 16MB
Maximum RAM: 136MB
RAM Slots: 2 168-pin
Minimum RAM Speed: 70 ns
RAM Sizes: 8, 16, 32, 64MB
Install in Groups of: 1

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 7.5.3
Original Enabler: System Enabler 410 v1.1

ROM ID: \$077D
ROM Version: \$29
ROM Size: 4MB
AppleTalk Version: 58.1.5

Supported Macintosh System Software:

<input type="checkbox"/> <1.0	<input type="checkbox"/> 6.0	<input type="checkbox"/> 6.0.8	<input type="checkbox"/> 7.1P2	<input type="checkbox"/> 7.1.2
<input type="checkbox"/> 1.0	<input type="checkbox"/> 6.0.1	<input type="checkbox"/> 7.0	<input type="checkbox"/> 7.1P3	<input type="checkbox"/> 7.5
<input type="checkbox"/> 1.1	<input type="checkbox"/> 6.0.2	<input type="checkbox"/> 7.0.1	<input type="checkbox"/> 7.1P5	<input type="checkbox"/> 7.5.1
<input type="checkbox"/> 2.0	<input type="checkbox"/> 6.0.3	<input type="checkbox"/> 7.0.1P	<input type="checkbox"/> 7.1P6	<input type="checkbox"/> 7.5.2
<input type="checkbox"/> 2.0.1	<input type="checkbox"/> 6.0.4	<input type="checkbox"/> 7.1	<input type="checkbox"/> 7.1.1 (Pro)	<input checked="" type="checkbox"/> 7.5.3
<input type="checkbox"/> 5.0	<input type="checkbox"/> 6.0.5	<input type="checkbox"/> 7.1P	<input type="checkbox"/> 7.1.1	<input checked="" type="checkbox"/> 7.5.5
<input type="checkbox"/> 5.1	<input type="checkbox"/> 6.0.7	<input type="checkbox"/> 7.1P1	<input type="checkbox"/> 7.1.2	<input checked="" type="checkbox"/> 7.6

SOUND

Built-in Microphone
Microphone Port Type: PlainTalk
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 2.4GB
Internal HD Interface: IDE
Original CD-ROM Speed: 8x