



System Fact Sheet

SYSTEM

Introduced: February 1997
Discontinued: n/a
Gestalt ID: 513
Form Factor: Performa 6400
Weight (lbs.): 44.5
Dimensions (inches): 16 H x 7.8 W x 16.9 D

POWER

Max. Watts: 220
Amps: 3.00
BTU Per Hour: 752.4
Voltage Range: 100-125/200-240
Freq'y Range (Hz): 47-63
Battery Type: 4.5V alkaline
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: 2
Ethernet: 10baseT
Microphone Port Type: PlainTalk
 Printer
 Modem
 Speaker
 Headphone
 Remote Control

VIDEO

Built-in Display: none
VRAM Speed: n/a
VRAM Needed: built in
Video Configuration: 2MB SGRAM

		<i>Maximum Color Bit-depth¹ At:</i>								
		512	640	640	640	800	832	1024	1152	1280
VRAM Speed:	VRAM Needed:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
		24	n/a	24	n/a	24	24	16	16	8

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGIC BOARD

Main Processor: 603e, 225 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 50 MHz
L1 Cache: 32K
L2 Cache: 256K
Secondary Processor: none
Slots: 2 PCI, Comm II, TV, video in

Some models ship with a modem in the comm slot II.

MEMORY

Memory on Logic Board: none
Minimum RAM: 32MB
Maximum RAM: 128MB
RAM Slots: 2 168-pin
Minimum RAM Speed: 60 ns
RAM Sizes: 4, 8, 16, 32, 64MB
Install in Groups of: 1

SOFTWARE

Speech Recognition Supported
Addressing Modes: 32-bit
Original SSW: 7.5.5
Original Enabler: System Enabler 411

ROM ID: \$077D
ROM Version: \$35
ROM Size: 4MB
AppleTalk Version: 60.1.1

Supported Macintosh System Software:

<input type="checkbox"/> <1.0	<input type="checkbox"/> 6.0	<input type="checkbox"/> 6.0.8	<input type="checkbox"/> 7.1P2	<input type="checkbox"/> 7.1.2
<input type="checkbox"/> 1.0	<input type="checkbox"/> 6.0.1	<input type="checkbox"/> 7.0	<input type="checkbox"/> 7.1P3	<input type="checkbox"/> 7.5
<input type="checkbox"/> 1.1	<input type="checkbox"/> 6.0.2	<input type="checkbox"/> 7.0.1	<input type="checkbox"/> 7.1P5	<input type="checkbox"/> 7.5.1
<input type="checkbox"/> 2.0	<input type="checkbox"/> 6.0.3	<input type="checkbox"/> 7.0.1P	<input type="checkbox"/> 7.1P6	<input type="checkbox"/> 7.5.2
<input type="checkbox"/> 2.0.1	<input type="checkbox"/> 6.0.4	<input type="checkbox"/> 7.1	<input type="checkbox"/> 7.1.1 (Pro)	<input type="checkbox"/> 7.5.3
<input type="checkbox"/> 5.0	<input type="checkbox"/> 6.0.5	<input type="checkbox"/> 7.1P	<input type="checkbox"/> 7.1.1	<input checked="" type="checkbox"/> 7.5.5
<input type="checkbox"/> 5.1	<input type="checkbox"/> 6.0.7	<input type="checkbox"/> 7.1P1	<input type="checkbox"/> 7.1.2	<input type="checkbox"/> 7.6

SOUND

Built-in Microphone
Microphone Port Type: PlainTalk
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

STORAGE

Supports Internal CD-ROM
Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 2, 3GB
Internal HD Interface: ATA
Original CD-ROM Speed: 12x