



System Fact Sheet

SYSTEM

Introduced: March 1994
Discontinued: January 1995
Gestalt ID: 112
Form Factor: IIvx
Weight (lbs.): 25
Dimensions (inches): 6 H x 13 W x 16.5 D

POWER

Max. Watts: 230
Amps: 1.90
BTU Per Hour: 786.6
Voltage Range: 100-240
Freq'y Range (Hz): 50-60
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15, HDI-45
Floppy: none
SCSI: DB-25
GeoPort Connectors: 2
Ethernet: AAUI-15
Microphone Port Type: PlainTalk

Printer **Speaker**
 Modem **Headphone**
 Remote Control

VIDEO **Built-in Display:** none

		<i>Maximum Color Bit-depth¹ At:</i>									
		512	640	640	640	800	832	1024	1152	1280	
VRAM Speed:	VRAM Needed:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024	
80 ns	built in	16	n/a	16	8	n/a	8	n/a	n/a	n/a	n/a
	built in	16	n/a	16	8	n/a	16	8	8	8	n/a
	4x256K	24	n/a	24	8	n/a	24	16	16	16	n/a

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGIC BOARD

Main Processor: 601, 66 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 33 MHz
L1 Cache: 32K
L2 Cache: opt'l.
Secondary Processor: none
Slots: 3 NuBus, PDS filled

MEMORY

Memory on Logic Board: 8MB
Minimum RAM: 8MB
Maximum RAM: 136MB
RAM Slots: 4 72-pin
Minimum RAM Speed: 80 ns
RAM Sizes: 4, 8, 16, 32MB
Install in Groups of: 2

SOFTWARE **Speech Recognition Supported**

Addressing Modes: 32-bit
Original SSW: 7.1.2
Original Enabler: PowerPC Enabler v1.0

ROM ID: \$077D
ROM Version: \$A4
ROM Size: 4MB
AppleTalk Version: 58.0.2

Supported Macintosh System Software:

<input type="checkbox"/> <1.0	<input type="checkbox"/> 6.0	<input type="checkbox"/> 6.0.8	<input type="checkbox"/> 7.1P2	<input type="checkbox"/> 7.1.2
<input type="checkbox"/> 1.0	<input type="checkbox"/> 6.0.1	<input type="checkbox"/> 7.0	<input type="checkbox"/> 7.1P3	<input checked="" type="checkbox"/> 7.5
<input type="checkbox"/> 1.1	<input type="checkbox"/> 6.0.2	<input type="checkbox"/> 7.0.1	<input type="checkbox"/> 7.1P5	<input checked="" type="checkbox"/> 7.5.1
<input type="checkbox"/> 2.0	<input type="checkbox"/> 6.0.3	<input type="checkbox"/> 7.0.1P	<input type="checkbox"/> 7.1P6	<input type="checkbox"/> 7.5.2
<input type="checkbox"/> 2.0.1	<input type="checkbox"/> 6.0.4	<input type="checkbox"/> 7.1	<input type="checkbox"/> 7.1.1 (Pro)	<input checked="" type="checkbox"/> 7.5.3
<input type="checkbox"/> 5.0	<input type="checkbox"/> 6.0.5	<input type="checkbox"/> 7.1P	<input type="checkbox"/> 7.1.1	<input checked="" type="checkbox"/> 7.5.5
<input type="checkbox"/> 5.1	<input type="checkbox"/> 6.0.7	<input type="checkbox"/> 7.1P1	<input checked="" type="checkbox"/> 7.1.2	<input checked="" type="checkbox"/> 7.6

SOUND

Built-in Microphone

Microphone Port Type: PlainTalk
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 250-500MB
Internal HD Interface: SCSI
Original CD-ROM Speed: 2x