



**System Fact Sheet**

**SYSTEM**

**Introduced:** April 1997  
**Discontinued:** n/a  
**Gestalt ID:** 515  
**Form Factor:** PM 4400  
**Weight (lbs.):** 24  
**Dimensions (inches):** 5.43 H x 15.12 W x 17.37 D

*This system is not sold in the U.S.*

**POWER**

**Max. Watts:** 150  
**Amps:** 3.00  
**BTU Per Hour:** 513  
**Voltage Range:** 110/220  
**Freq'y Range (Hz):** 47-63  
**Battery Type:** 4.5V alkaline  
 **Soft Power**  
 **Monitor Power Outlet**

**PORTS**

**ADB:** 1  
**Video:** DB-15  
**Floppy:** none  
**SCSI:** DB-25  
**GeoPort Connectors:** 2  
**Ethernet:** 10baseT  
**Microphone Port Type:** PlainTalk  
 **Printer**       **Speaker**  
 **Modem**       **Headphone**  
 **Remote Control**

*Includes PC game port on PC Compatibility card.*

**VIDEO**

**Built-in Display:** none

**Maximum Color Bit-depth<sup>1</sup> At:**

VRAM Speed:	VRAM Needed:	Video Configuration:	512 x384	640 x400	640 x480	640 x870 <sup>2</sup>	800 x600	832 x624	1024 x768	1152 x870	1280 x1024
n/a	1x2MB	2MB EDO DRAM	24	n/a	24	8	24	16	16	16	8
	1x4MB	4MB SGRAM	24	n/a	24	8	24	24	24	16	16

<sup>1</sup> 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

<sup>2</sup> The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

**LOGIC BOARD**

**Main Processor:** 603e, 200 MHz  
**PMMU:** integrated  
**FPU:** integrated  
**Data Path:** 64-bit, 40 MHz  
**L1 Cache:** 32K  
**L2 Cache:** 256K  
**Secondary Processor:** Cyrix P166 6x86  
**Slots:** 2 PCI, comm II

*Supports one 7-inch and one 12-inch PCI slot. The 12-inch PCI slot is occupied by the PC Compatibility card.*

**MEMORY**

**Memory on Logic Board:** none  
**Minimum RAM:** 32MB  
**Maximum RAM:** 160MB  
**RAM Slots:** 3 168-pin  
**Minimum RAM Speed:** 60 ns  
**RAM Sizes:** 8, 16, 32, 64MB  
**Install in Groups of:** 1

*Uses JEDEC-standard 3.3-volt unbuffered EDO DIMM devices. DRAM slot 1 supports only single-bank DIMMs.*

**SOFTWARE**

**Speech Recognition Supported**

**Addressing Modes:** 32-bit  
**Original SSW:** 7.5.3  
**Original Enabler:** System Enabler 827

**ROM ID:** \$077D  
**ROM Version:** \$3A  
**ROM Size:** 4MB  
**AppleTalk Version:** 60.1.1

**Supported Macintosh System Software:**

- <1.0     6.0     6.0.8     7.1P2     7.1.2
- 1.0     6.0.1     7.0     7.1P3     7.5
- 1.1     6.0.2     7.0.1     7.1P5     7.5.1
- 2.0     6.0.3     7.0.1P     7.1P6     7.5.2
- 2.0.1     6.0.4     7.1     7.1.1 (Pro)     7.5.3
- 5.0     6.0.5     7.1P     7.1.1     7.5.5
- 5.1     6.0.7     7.1P1     7.1.2     7.6

*Includes Windows 95 for use with PC Compatibility card.*

**SOUND**

**Microphone Port Type:** PlainTalk  
 **Built-in Microphone**  
**Sound In:** stereo, 16-bit  
**Sound Out:** stereo, 16-bit

**STORAGE**

**Supports Internal CD-ROM**

**Floppy Size:** 1.44MB  
**Floppy Inject:** manual  
**Internal HD Size:** 2GB  
**Internal HD Interface:** ATA  
**Original CD-ROM Speed:** 12x