



System Fact Sheet

SYSTEM

Introduced: February 1997
Discontinued: n/a
Gestalt ID: 515
Form Factor: PM 4400
Weight (lbs.): 24
Dimensions (inches): 5.43 H x 15.12 W x 17.37 D

This system is not sold in the U.S.

POWER

Max. Watts: 150
Amps: 3.00
BTU Per Hour: 513
Voltage Range: 110/220
Freq'y Range (Hz): 47-63
Battery Type: 4.5V alkaline
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: 2
Ethernet: 10baseT
Microphone Port Type: PlainTalk
 Printer
 Modem
 Speaker
 Headphone
 Remote Control

VIDEO

Built-in Display: none

Maximum Color Bit-depth¹ At:

VRAM Speed:	VRAM Needed:	Video Configuration:	512	640	640	640	800	832	1024	1152	1280
x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024			
n/a	1x2MB	2MB EDO DRAM	24	n/a	24	8	24	16	16	16	8
	1x4MB	4MB SGRAM	24	n/a	24	8	24	24	24	16	16

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGIC BOARD

Main Processor: 603e, 200 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 40 MHz
L1 Cache: 32K
L2 Cache: 256K
Secondary Processor: none
Slots: 2 PCI, comm II

Supports one 7-inch and one 12-inch PCI slot.

MEMORY

Memory on Logic Board: none
Minimum RAM: 16MB
Maximum RAM: 160MB
RAM Slots: 3 168-pin
Minimum RAM Speed: 60 ns
RAM Sizes: 8, 16, 32, 64MB
Install in Groups of: 1

Uses JEDEC-standard 3.3-volt unbuffered EDO DIMM devices. DRAM slot 1 supports only single-bank DIMMs.

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 7.5.3
Original Enabler: System Enabler 827

ROM ID: \$077D
ROM Version: \$3A
ROM Size: 4MB
AppleTalk Version: 60.1.1

Supported Macintosh System Software:

<1.0 6.0 6.0.8 7.1P2 7.1.2
 1.0 6.0.1 7.0 7.1P3 7.5
 1.1 6.0.2 7.0.1 7.1P5 7.5.1
 2.0 6.0.3 7.0.1P 7.1P6 7.5.2
 2.0.1 6.0.4 7.1 7.1.1 (Pro) 7.5.3
 5.0 6.0.5 7.1P 7.1.1 7.5.5
 5.1 6.0.7 7.1P1 7.1.2 7.6

SOUND

Built-in Microphone
Microphone Port Type: PlainTalk
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 2GB
Internal HD Interface: ATA
Original CD-ROM Speed: 8x