



System Fact Sheet

SYSTEM	POWER	PORTS
Introduced: March 1994 Discontinued: May 1995 Gestalt ID: 119 Form Factor: Centris 610 Weight (lbs.): 14 Dimensions (inches): 3.4 H x 16.3 W x 15.6 D	Max. Watts: 86 Amps: 1.70 BTU Per Hour: 294.12 Voltage Range: 100-240 Freq'y Range (Hz): 47-63 Battery Type: 3.6V lithium <input type="checkbox"/> Soft Power <input checked="" type="checkbox"/> Monitor Power Outlet	ADB: 2 Video: DB-15 Floppy: none SCSI: DB-25 GeoPort Connectors: none Ethernet: opt. AAUI-15 Microphone Port Type: Omni <input checked="" type="checkbox"/> Printer <input checked="" type="checkbox"/> Modem <input checked="" type="checkbox"/> Speaker <input type="checkbox"/> Headphone <input type="checkbox"/> Remote Control

VIDEO	Built-in Display: none	Maximum Color Bit-depth ¹ At:
VRAM Speed:	VRAM Needed:	Video Configuration:
100 ns	built in	512K VRAM
	2x256K	1MB VRAM
		512 640 640 640 800 832 1024 1152 1280
		x384 x400 x480 x870 ² x600 x624 x768 x870 x1024
		16 n/a 8 4 8 8 4 4 n/a
		16 n/a 16 8 16 16 8 8 n/a

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGIC BOARD	MEMORY
Main Processor: 601, 40 MHz PMMU: integrated FPU: integrated Data Path: 64-bit, 20 MHz L1 Cache: 32K L2 Cache: 1MB Secondary Processor: 68040, 40/20 MHz Slots: PDS filled	Memory on Logic Board: 4MB Minimum RAM: 4MB Maximum RAM: 68MB RAM Slots: 2 72-pin Minimum RAM Speed: 80 ns RAM Sizes: 4, 8, 16, 32MB Install in Groups of: 1

This configuration is achieved by installing the Power Macintosh Upgrade Card.

SOFTWARE	Speech Recognition Supported	Supported Macintosh System Software:
Addressing Modes: 32-bit Original SSW: 7.1.2 Original Enabler: PowerPC Upgrade Card Enabler	ROM ID: \$077D ROM Version: n/a ROM Size: 4MB AppleTalk Version: 58.0.2	<input type="checkbox"/> <1.0 <input type="checkbox"/> 6.0 <input type="checkbox"/> 6.0.8 <input type="checkbox"/> 7.1P2 <input type="checkbox"/> 7.1.2 <input type="checkbox"/> 1.0 <input type="checkbox"/> 6.0.1 <input type="checkbox"/> 7.0 <input type="checkbox"/> 7.1P3 <input checked="" type="checkbox"/> 7.5 <input type="checkbox"/> 1.1 <input type="checkbox"/> 6.0.2 <input type="checkbox"/> 7.0.1 <input type="checkbox"/> 7.1P5 <input checked="" type="checkbox"/> 7.5.1 <input type="checkbox"/> 2.0 <input type="checkbox"/> 6.0.3 <input type="checkbox"/> 7.0.1P <input type="checkbox"/> 7.1P6 <input type="checkbox"/> 7.5.2 <input type="checkbox"/> 2.0.1 <input type="checkbox"/> 6.0.4 <input type="checkbox"/> 7.1 <input type="checkbox"/> 7.1.1 (Pro) <input checked="" type="checkbox"/> 7.5.3 <input type="checkbox"/> 5.0 <input type="checkbox"/> 6.0.5 <input type="checkbox"/> 7.1P <input type="checkbox"/> 7.1.1 <input checked="" type="checkbox"/> 7.5.5 <input type="checkbox"/> 5.1 <input type="checkbox"/> 6.0.7 <input type="checkbox"/> 7.1P1 <input checked="" type="checkbox"/> 7.1.2 <input checked="" type="checkbox"/> 7.6

SOUND	STORAGE
<input type="checkbox"/> Built-in Microphone Microphone Port Type: Omni Sound In: mono, 8-bit Sound Out: stereo, 8-bit	<input checked="" type="checkbox"/> Supports Internal CD-ROM Floppy Size: 1.44MB Floppy Inject: auto Internal HD Size: 80-500MB Internal HD Interface: SCSI Original CD-ROM Speed: 2x