



System Fact Sheet

SYSTEM

Introduced: April 1998
Discontinued:
Gestalt ID: 510
Form Factor: PM G3
Weight (lbs.): 59.5
Dimensions (inches): 19.92 H x 16.08 W x 18 D

POWER

Max. Watts: 300
Amps:
BTU Per Hour: 1026
Voltage Range: 90-264
Freq'y Range (Hz): 50-60
Battery Type: 3.6V Lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: none
Floppy: HDI-20
SCSI: DB-25
GeoPort Connectors: 1
Ethernet: 10Base-T
Microphone Port Type: Internal
 Printer
 Modem
 Speaker
 Headphone
 Remote Control

VIDEO

Built-in Display: none

Maximum Color Bit-depth¹ At:

	512	640	640	640	800	832	1024	1152	1280
VRAM Speed:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
VRAM Needed:									
Video Configuration:									

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGIC BOARD

Main Processor: G3, 233/266
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 66Mhz
L1 Cache: 32K
L2 Cache: 512K
Secondary Processor: none
Slots: 3 PCIs

MEMORY

Memory on Logic Board: none
Minimum RAM: 32MB
Maximum RAM: 384MB
RAM Slots: 168-pin
Minimum RAM Speed: 10ns
RAM Sizes: 8, 16, 32, 64, 128MB
Install in Groups of: 1

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 8.0
Original Enabler:

ROM ID:
ROM Version:
ROM Size: 4MB
AppleTalk Version:

Supported Macintosh System Software:

- | | | | | |
|--------------------------------|--------------------------------|---------------------------------|--------------------------------------|--------------------------------|
| <input type="checkbox"/> <1.0 | <input type="checkbox"/> 6.0 | <input type="checkbox"/> 6.0.8 | <input type="checkbox"/> 7.1P2 | <input type="checkbox"/> 7.1.2 |
| <input type="checkbox"/> 1.0 | <input type="checkbox"/> 6.0.1 | <input type="checkbox"/> 7.0 | <input type="checkbox"/> 7.1P3 | <input type="checkbox"/> 7.5 |
| <input type="checkbox"/> 1.1 | <input type="checkbox"/> 6.0.2 | <input type="checkbox"/> 7.0.1 | <input type="checkbox"/> 7.1P5 | <input type="checkbox"/> 7.5.1 |
| <input type="checkbox"/> 2.0 | <input type="checkbox"/> 6.0.3 | <input type="checkbox"/> 7.0.1P | <input type="checkbox"/> 7.1P6 | <input type="checkbox"/> 7.5.2 |
| <input type="checkbox"/> 2.0.1 | <input type="checkbox"/> 6.0.4 | <input type="checkbox"/> 7.1 | <input type="checkbox"/> 7.1.1 (Pro) | <input type="checkbox"/> 7.5.3 |
| <input type="checkbox"/> 5.0 | <input type="checkbox"/> 6.0.5 | <input type="checkbox"/> 7.1P | <input type="checkbox"/> 7.1.1 | <input type="checkbox"/> 7.5.5 |
| <input type="checkbox"/> 5.1 | <input type="checkbox"/> 6.0.7 | <input type="checkbox"/> 7.1P1 | <input type="checkbox"/> 7.1.2 | <input type="checkbox"/> 7.6 |

SOUND

Microphone Port Type: Internal
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

Built-in Microphone

STORAGE

Floppy Size: 1.44
Floppy Inject: manual
Internal HD Size: 4GB
Internal HD Interface: ATA
Original CD-ROM Speed: 24x

Supports Internal CD-ROM