

Workgroup Server 9650/233

System Fact Sheet

| Oystelli i ac | | | | | | | | |
|--|--|---|--|---|--|---------------------------------|---|-------------------------|
| Gestalt ID: 67 Form Factor: PM 9600 Weight (lbs.): 35 Dimensions (inches): 17.3 H x 9.7 W x 17.3 D Battery T | | | 3.00 1333.8 100-125/200 | PORTESADB: 1Video: DB-15Flopy: noneSCSI: DB-25GeoPort Connectors: 2Chernet: AAUI, 10baseTMotore Port Type: PlainTalkSpeakerOrinterModenHeadphoneControl | | | | |
| Maximum Color Bit-depthVICEOBuilt-in Display: noneMaximum Color Bit-depthAt:VRAM Speed:VRAM Neede1:Video Configuration: 512 640 640 640 800 832 1024 1152 1280 N/an/an/avideo card (4MB) 24 n/a 24 8 24 < | | | | | | | | |
| LOGEC BOARD Main Processor: 604e, 233 MHz PMMU: integrated FPU: integrated Data Path: 64-bit, 50 MHz L1 Cache: 64K L2 Cache: 512K Secondary Processor: opt. PC Compatbility Card Slots: 6 PCI | | | Memory on Logic Board: none Minimum RAM: 64MB Maximum RAM: 768MB RAM Slots: 12 168-pin Minimum RAM Speed: 70 ns RAM Sizes: 8, 16, 32, 64MB Install in Groups of: 1 | | | | | |
| Original SSW: 7.6.1 ROM Vers | | | Size: $4MB$ 2.0 $6.0.3$ $7.0.1P$ $7.1P6$ $7.5.2$ 2.01 $6.0.4$ 7.1 $7.1P6$ $7.5.2$ | | | | | |
| Sound | | r pe: PlainTalk In: stereo, 16-bit Dut: stereo, 16-bit | STORAGE Support Interna CD-RO | ts I | | Flopp Internal ernal HD I | ppy Size: 1.4 y Inject: ma HD Size: 40 nterface: 80 M Speed: 12 | nual B, 2x4GB CSI |