



System Fact Sheet

SYSTEM

Introduced: October 1991
Discontinued: September 1993
Gestalt ID: 23
Form Factor: Classic
Weight (lbs.): 16
Dimensions (inches): 13.2 H x 9.7 W x 11.2 D

Codename: Montana, Apollo
Order Number:
KB Article #: 9547

Support Discontinued 9/1/98

POWER

Max. Watts: 76
Amps: 0.63
BTU Per Hour: 259.92
Voltage Range: 120
Freq'y Range (Hz): 47-63
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: none
Floppy: DB-19
SCSI: DB-25
GeoPort Connectors: none
Ethernet: none
Microphone Port Type: Omni

Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

VIDEO

Built-in Display: 9" monochrome CRT

VRAM Speed:	VRAM Needed:	Video Configuration:	512	640	640	640	800	832	1024	1152	1280
n/a	built in	built-in CRT	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
			1	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a

Maximum Color Bit-depth¹ At:

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.
Screen size is 512x342.

LOGICBOARD

Main Processor: 68030, 16 MHz
PMMU: integrated
FPU: none
Data Path: 16-bit, 16 MHz
L1 Cache: 0.5K
L2 Cache: none
Secondary Processor: none
Slots: none

MEMORY

Memory on Logic Board: 2 MB
Minimum RAM: 2 MB
Maximum RAM: 10 MB
RAM Slots: 2 30-pin
Minimum RAM Speed: 100 ns
RAM Sizes: 1, 2, 4 MB
Install in Groups of: 2

SOFTWARE

Speech Recognition Supported

Addressing Modes: 24-, 32-bit
Original SSW: 7.0.1
Original Enabler: none

ROM ID: \$067C
ROM Version: n/a
ROM Size: 512K
AppleTalk Version: 56.0.2

Supported Macintosh System Software:

<input type="checkbox"/> A/UX 1.0	<input type="checkbox"/> NOS 1.11	<input type="checkbox"/> ProDOS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 1.11	<input type="checkbox"/> NOS 1.3	<input type="checkbox"/> GS/OS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 2.0	<input type="checkbox"/> NOS 2.0	<input type="checkbox"/> NeXTStep 1.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 3.0.1	<input type="checkbox"/> NOS 2.1	<input type="checkbox"/> NeXTStep 2.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4	<input type="checkbox"/> LOS 7/7	<input type="checkbox"/> NeXTStep 3.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4.1	<input type="checkbox"/> DOS 3.1	<input type="checkbox"/> OpenStep	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.5	<input type="checkbox"/> SOS 1.3	<input type="checkbox"/> <1.0	<input type="checkbox"/>

SOUND

Built-in Microphone

Microphone Port Type: Omni
Sound In: mono, 8-bit
Sound Out: mono, 8-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: auto
Internal HD Size: 40-80MB
Internal HD Interface: SCSI
Original CD-ROM Speed:

HISTORY

Introduced in October 1991, The Mac Classic II was everything the original Classic should have been. It shipped in a restyled case, had a 16 MHz 68030 processor, and included a microphone. The Classic II cost \$1,900 and was discontinued in September 1993. It was bundled with a 2400/9600 baud fax/modem and extra software and sold as the Performa 200 in September 1992. The Performa 200 was discontinued in April 1993.