



System Fact Sheet

SYSTEM

Introduced: February 1993
Discontinued: May 1994
Gestalt ID: 49
Form Factor: Color Classic
Weight (lbs.): 22.5
Dimensions (inches): 14.5 H x 9.9 W x 12.6 D

Codename: Slice
Oder Number: M1600LL/A
KB Article #:

POWER

Max. Watts: 100
Amps: 0.83
BTU Per Hour: 342
Voltage Range: 90-240
Freq'y Range (Hz): 47-63
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 2
Video: none
Floppy: none
SCSI: DB-25
GeoPort Connectors: none
Ethernet: none
Microphone Port Type: Omni

Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

VIDEO **Built-in Display:** 10" Sony Trinitron RGB

			<i>Maximum Color Bit-depth¹ At:</i>								
			512	640	640	640	800	832	1024	1152	1280
VRAM Speed:	VRAM Needed:	Video Configuration:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
100 ns	built in	256K VRAM	8	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	1x256K	512K VRAM	16	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGICBOARD

Main Processor: 68030, 16 MHz
PMMU: integrated
FPU: opt. 68882
Data Path: 16-bit, 16 MHz
L1 Cache: 0.5K
L2 Cache: none
Secondary Processor: none
Slots: 1 LC PDS

MEMORY

Memory on Logic Board: 4 MB
Minimum RAM: 4 MB
Maximum RAM: 10MB
RAM Slots: 2 30-pin
Minimum RAM Speed: 100 ns
RAM Sizes: 1, 2, 4 MB
Install in Groups of: 2

When all SIMM slots are filled with 4MB SIMMs, the lower 2MB of RAM on the logic board cannot be addressed.

SOFTWARE **Speech Recognition Supported**

Addressing Modes: 24-, 32-bit
Original SSW: 7.1
Original Enabler: System Enabler 401

ROM ID: \$067C
ROM Version: \$24
ROM Size: 1MB
AppleTalk Version: 57.0.4

Supported Macintosh System Software:

<input type="checkbox"/> A/UX 1.0	<input type="checkbox"/> NOS 1.11	<input type="checkbox"/> ProDOS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 1.11	<input type="checkbox"/> NOS 1.3	<input type="checkbox"/> GS/OS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 2.0	<input type="checkbox"/> NOS 2.0	<input type="checkbox"/> NeXTStep 1.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 3.0.1	<input type="checkbox"/> NOS 2.1	<input type="checkbox"/> NeXTStep 2.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4	<input type="checkbox"/> LOS 7/7	<input type="checkbox"/> NeXTStep 3.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4.1	<input type="checkbox"/> DOS 3.1	<input type="checkbox"/> OpenStep	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.5	<input type="checkbox"/> SOS 1.3	<input type="checkbox"/> <1.0	<input type="checkbox"/>

SOUND

Built-in Microphone

Microphone Port Type: Omni
Sound In: mono, 8-bit
Sound Out: mono, 8-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: auto
Internal HD Size: 40-160MB
Internal HD Interface: SCSI
Original CD-ROM Speed:

HISTORY

Released in February 1993, the Color Classic was identical to the Classic II, except for a color screen, a larger ROM, and a restyled case. The Color Classic sold for \$1,390, and was also released as the Performa 250.