



System Fact Sheet

SYSTEM

Introduced: March 1989
Discontinued: March 1991
Gestalt ID: 8
Form Factor: IIcx
Weight (lbs.): 13.6
Dimensions (inches): 5.5 H x 11.9 W x 14.4 D

Codename: Aurora, Cobra, Atlantic
Order Number: M5650LL/A
KB Article #: 3511, 3512

Support Discontinued 9/1/98

POWER

Max. Watts: 159
Amps: 1.30
BTU Per Hour: 543.78
Voltage Range: 100-240
Freq'y Range (Hz): 50-60
Battery Type: 3.6V lithium

Soft Power
 Monitor Power Outlet

PORTS

ADB: 2
Video: none
Floppy: DB-19
SCSI: DB-25

GeoPort Connectors: none
Ethernet: none

Microphone Port Type: none

Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

VIDEO

Built-in Display: none

VRAM Speed: n/a **VRAM Needed:** n/a **Video Configuration:** requires video card

	512	640	640	640	800	832	1024	1152	1280
	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a

Maximum Color Bit-depth¹ At:

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGICBOARD

Main Processor: 68030, 16 MHz
PMMU: integrated
FPU: 68882
Data Path: 32-bit, 16 MHz
L1 Cache: 0.5K
L2 Cache: none
Secondary Processor: none
Slots: 3 NuBus

MEMORY

Memory on Logic Board: none
Minimum RAM: 1 MB
Maximum RAM: 128 MB
RAM Slots: 8 30-pin
Minimum RAM Speed: 120 ns
RAM Sizes: 256 K, 1, 4, 16 MB
Install in Groups of: 4

SOFTWARE

Speech Recognition Supported

Addressing Modes: 24-bit
Original SSW: 6.0.3
Original Enabler: none

ROM ID: \$0178
ROM Version: n/a
ROM Size: 256K
AppleTalk Version: 49

Supported Macintosh System Software:

<input type="checkbox"/> A/UX 1.0	<input type="checkbox"/> NOS 1.11	<input type="checkbox"/> ProDOS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 1.11	<input type="checkbox"/> NOS 1.3	<input type="checkbox"/> GS/OS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 2.0	<input type="checkbox"/> NOS 2.0	<input type="checkbox"/> NeXTStep 1.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 3.0.1	<input type="checkbox"/> NOS 2.1	<input type="checkbox"/> NeXTStep 2.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4	<input type="checkbox"/> LOS 7/7	<input type="checkbox"/> NeXTStep 3.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4.1	<input type="checkbox"/> DOS 3.1	<input type="checkbox"/> OpenStep	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.5	<input type="checkbox"/> SOS 1.3	<input type="checkbox"/> <1.0	<input type="checkbox"/>

SOUND

Built-in Microphone

Microphone Port Type: none
Sound In: none
Sound Out: stereo, 8-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: auto
Internal HD Size: 40-80MB
Internal HD Interface: SCSI
Original CD-ROM Speed:

HISTORY

Essentially a IIx in a smaller case and with 3 fewer NuBus slots, The IIcx sold for \$5369.