



System Fact Sheet

SYSTEM

Introduced: October 1993
Discontinued: February 1994
Gestalt ID: 83
Form Factor: Color Classic
Weight (lbs.): 22.5
Dimensions (inches): 14.5 H x 9.9 W x 12.6 D

Codename:
Order Number:
KB Article #:

This system is not sold in the U.S. as the Color Classic II, but WAS sold in the U.S. as the Performa 275.

POWER

Max. Watts: 100
Amps: 0.83
BTU Per Hour: 342
Voltage Range: 90-240
Freq'y Range (Hz): 47-63
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 2
Video: none
Floppy: none
SCSI: DB-25
GeoPort Connectors: none
Ethernet: none
Microphone Port Type: Omni
 Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

VIDEO

Built-in Display: 10" Sony Trinitron RGB

Maximum Color Bit-depth¹ At:

VRAM Speed:	VRAM Needed:	Video Configuration:	512	640	640	640	800	832	1024	1152	1280
x384	x400	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024	
80 ns	built in	256K VRAM	8	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	1x256K	512K VRAM	16	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGICBOARD

Main Processor: 68030, 33 MHz
PMMU: integrated
FPU: opt. 68882
Data Path: 32-bit, 33 MHz
L1 Cache: 0.5K
L2 Cache: none
Secondary Processor: none
Slots: 1 LC PDS

MEMORY

Memory on Logic Board: 4 MB
Minimum RAM: 4 MB
Maximum RAM: 36 MB
RAM Slots: 1 72-pin
Minimum RAM Speed: 80 ns
RAM Sizes: 1, 2, 4, 8, 16, 32 MB
Install in Groups of: 1

SOFTWARE

Speech Recognition Supported

Addressing Modes: 24-, 32-bit
Original SSW: J-7.1
Original Enabler: System Enabler 403

ROM ID: \$067C
ROM Version: \$24
ROM Size: 1MB
AppleTalk Version: 57.0.4

Supported Macintosh System Software:

- | | | | |
|---------------------------------------|-----------------------------------|---------------------------------------|--------------------------|
| <input type="checkbox"/> A/UX 1.0 | <input type="checkbox"/> NOS 1.11 | <input type="checkbox"/> ProDOS | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 1.11 | <input type="checkbox"/> NOS 1.3 | <input type="checkbox"/> GS/OS | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 2.0 | <input type="checkbox"/> NOS 2.0 | <input type="checkbox"/> NeXTStep 1.x | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 3.0.1 | <input type="checkbox"/> NOS 2.1 | <input type="checkbox"/> NeXTStep 2.x | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 4.1.4 | <input type="checkbox"/> LOS 7/7 | <input type="checkbox"/> NeXTStep 3.x | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 4.1.4.1 | <input type="checkbox"/> DOS 3.1 | <input type="checkbox"/> OpenStep | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 4.1.5 | <input type="checkbox"/> SOS 1.3 | <input type="checkbox"/> <1.0 | <input type="checkbox"/> |

SOUND

Microphone Port Type: Omni
Sound In: mono, 8-bit
Sound Out: stereo, 8-bit

Built-in Microphone

STORAGE

Floppy Size: 1.44MB
Floppy Inject: auto
Internal HD Size: 80-160MB
Internal HD Interface: SCSI
Original CD-ROM Speed:

Supports Internal CD-ROM

HISTORY

Released only in Japan, the Color Classic II improved on the original Color Classic by doubling both the processor speed to 33 Mhz and the data path to 32-bit. Also added was stereo sound output. It was also released in the US as the Performa 275.