



System Fact Sheet

SYSTEM

Introduced: October 1993
Discontinued: October 1994
Gestalt ID: 89
Form Factor: LC
Weight (lbs.): 8.8
Dimensions (inches): 2.9 H x 12.2 W x 15.3 D

Codename: Aladdin, Primus
Order Number: M1904LL/A
KB Article #: 15507, 13577

POWER

Max. Watts: 50
Amps: 0.25
BTU Per Hour: 171
Voltage Range: 100-240
Freq'y Range (Hz): 47-63
Battery Type: 3.6V lithium

Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: none
Ethernet: none
Microphone Port Type: PlainTalk

Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

VIDEO **Built-in Display:** none

		<i>Maximum Color Bit-depth¹ At:</i>									
		512	640	640	640	800	832	1024	1152	1280	
VRAM Speed:	VRAM Needed:	Video Configuration:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
80 ns	2x256K	512K VRAM	16	n/a	8	4	n/a	8	4	4	n/a
	2x512K	1MB VRAM	16	n/a	16	8	n/a	16	8	8	n/a

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGICBOARD

Main Processor: 68LC040, 50 MHz
PMMU: integrated
FPU: none
Data Path: 32-bit, 25 MHz
L1 Cache: 8K
L2 Cache: none
Secondary Processor: none
Slots: 1 LC PDS

MEMORY

Memory on Logic Board: 4 MB
Minimum RAM: 4 MB
Maximum RAM: 36 MB
RAM Slots: 1 72-pin
Minimum RAM Speed: 80 ns
RAM Sizes: 1, 2, 4, 8, 16, 32 MB
Install in Groups of: 1

SOFTWARE **Speech Recognition Supported**

Addressing Modes: 24-, 32-bit
Original SSW: 7.1P3
Original Enabler: System Enabler 364

ROM ID: \$067C
ROM Version: n/a
ROM Size: 1MB
AppleTalk Version: 57.0.4

Supported Macintosh System Software:

<input type="checkbox"/> A/UX 1.0	<input type="checkbox"/> NOS 1.11	<input type="checkbox"/> ProDOS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 1.11	<input type="checkbox"/> NOS 1.3	<input type="checkbox"/> GS/OS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 2.0	<input type="checkbox"/> NOS 2.0	<input type="checkbox"/> NeXTStep 1.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 3.0.1	<input type="checkbox"/> NOS 2.1	<input type="checkbox"/> NeXTStep 2.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4	<input type="checkbox"/> LOS 7/7	<input type="checkbox"/> NeXTStep 3.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4.1	<input type="checkbox"/> DOS 3.1	<input type="checkbox"/> OpenStep	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.5	<input type="checkbox"/> SOS 1.3	<input type="checkbox"/> <1.0	<input type="checkbox"/>

SOUND

Built-in Microphone

Microphone Port Type: PlainTalk
Sound In: mono, 8-bit
Sound Out: stereo, 8-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 160-230MB
Internal HD Interface: SCSI
Original CD-ROM Speed:

HISTORY

The most affordable Quadra ever, the 605 was released in October 1993. It had a 25 MHz 68LC040 processor, and came in a small newly designed case. It sold for \$900 and was discontinued in October 1994. It was also sold as the LC 475, and as Performas 475 and 476 which were bundled with various combinations of a fax/modems, monitors, and hard drives.