



### System Fact Sheet

#### SYSTEM

**Introduced:** April 1996  
**Discontinued:** April 1997  
**Gestalt ID:** 41  
**Form Factor:** PM 5200  
**Weight (lbs.):** 45  
**Dimensions (inches):** 17.5 H x 15.1 W x 16 D

**Codename:** Trailblazer, Bongo,  
**Order Number:**  
**KB Article #:**

*This system is not sold in the U.S.*

#### POWER

**Max. Watts:** 125  
**Amps:** 4.00  
**BTU Per Hour:** 427.5  
**Voltage Range:** 110-240  
**Freq'y Range (Hz):** 50-60  
**Battery Type:** 4.5V alkaline

**Soft Power**  
 **Monitor Power Outlet**

#### PORTS

**ADB:** 1  
**Video:** opt. DB-15  
**Floppy:** none  
**SCSI:** DB-25  
**GeoPort Connectors:** none  
**Ethernet:** none  
**Microphone Port Type:** PlainTalk

**Printer**     **Speaker**  
 **Modem**     **Headphone**  
 **Airport**     **Remote Control**

#### VIDEO

VRAM Speed:	VRAM Needed:	Video Configuration:	Maximum Color Bit-depth <sup>1</sup> At:								
			512	640	640	640	800	832	1024	1152	1280
60 ns	built in	1MB DRAM	x384	x400	x480	x870 <sup>2</sup>	x600	x624	x768	x870	x1024
			n/a	n/a	16	n/a	n/a	n/a	n/a	n/a	n/a

<sup>1</sup> 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

<sup>2</sup> The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

#### LOGICBOARD

**Main Processor:** 603e, 100 MHz  
**PMMU:** integrated  
**FPU:** integrated  
**Data Path:** 64-bit, 40 MHz  
**L1 Cache:** 32K  
**L2 Cache:** opt'l.  
**Secondary Processor:** none  
**Slots:** LC, comm, TV, video in/out

#### MEMORY

**Memory on Logic Board:** none  
**Minimum RAM:** 8 MB  
**Maximum RAM:** 64 MB  
**RAM Slots:** 2 72-pin  
**Minimum RAM Speed:** 80 ns  
**RAM Sizes:** 4, 8, 16, 32 MB  
**Install in Groups of:** 1

#### SOFTWARE

**Speech Recognition Supported**

**Addressing Modes:** 32-bit  
**Original SSW:** 7.5.3  
**Original Enabler:** none

**ROM ID:** \$077D  
**ROM Version:** n/a  
**ROM Size:** 4MB  
**AppleTalk Version:** n/a

#### SUPPORTED MACINTOSH SYSTEM SOFTWARE:

<input type="checkbox"/> A/UX 1.0	<input type="checkbox"/> NOS 1.11	<input type="checkbox"/> ProDOS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 1.11	<input type="checkbox"/> NOS 1.3	<input type="checkbox"/> GS/OS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 2.0	<input type="checkbox"/> NOS 2.0	<input type="checkbox"/> NeXTStep 1.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 3.0.1	<input type="checkbox"/> NOS 2.1	<input type="checkbox"/> NeXTStep 2.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4	<input type="checkbox"/> LOS 7/7	<input type="checkbox"/> NeXTStep 3.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4.1	<input type="checkbox"/> DOS 3.1	<input type="checkbox"/> OpenStep	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.5	<input type="checkbox"/> SOS 1.3	<input type="checkbox"/> <1.0	<input type="checkbox"/>

#### SOUND

**Built-in Microphone**

**Microphone Port Type:** PlainTalk  
**Sound In:** mono, 16-bit  
**Sound Out:** stereo, 16-bit

*INPUT: impedance 100 kOhm; avg. line level 100 mV rms; avg. mic. level 70 mV rms, max. input level 1.8 V rms*

#### STORAGE

**Supports Internal CD-ROM**

**Floppy Size:** 1.44MB  
**Floppy Inject:** manual  
**Internal HD Size:** 1.2GB  
**Internal HD Interface:** IDE  
**Original CD-ROM Speed:** 4x

#### HISTORY

Introduced in April 1995, The 5200 LC was the first LC model with a PowerPC chip. Released initially only in educational markets, the 5200 LC was powered by a 75 Mhz 603 processor, a lower voltage variant of the 601, and came in a restyled LC 550 all-in-one case. It sold for \$2000, and was replaced in April 1996 by the faster 5260, which had a 100 Mhz 603e and was available in consumer markets (The 5260 had a smaller 14" Monitor.). The 5200 was also released in Apple's Performa line as the Performas 5200CD, 5210CD, 5215CD, 5220CD, 5260CD, 5270CD, 5280CD, 5300CD and 5320CD, each of which had different hardware and software bundles. There was also a 5300 LC and 5320 LC released to the educational market, which had the same design but with 100 and 120 Mhz 603e's, respectively and different hardware and software bundles. all have now been discontinued.