

Macintosh Performa 5440

SISTEM

VDEO

Introduced: November 1996 **Discontinued:** April 1998 Gestalt ID: 74 Form Factor: PM 5200 Weight (lbs.): 47

Dimensions (inches): 17.5 H x 15.1 W x 16 D

Codename: Excalibur, Chimera

Oder Number: KB Article #:

This system is not sold in the U.S.

POWER

Max. Watts: 220 **Amps:** 4.00 BTU Per Hour: 752.4 Voltage Range: 110-240 Freq'y Range (Hz): 50-60 Battery Type: 4.5V alkaline

> **⊠** Soft Power **☐** Monitor Power Outlet

PORIS

ADB: 1 Video: DB-15 Floppy: none SCSI: DB-25 **GeoPort Connectors: 2**

Ethernet: none

Microphone Port Type: PlainTalk **⊠** Printer **⊠** Speaker

Modem **Headphone** ☐ Airport **⊠** Remote Control

Maximum Color Bit-depth¹ At: Built-in Display: 15" shadow mask RGB

640 640 800 832 1024 1152 1280 512 VRAM Speed: VRAM Needed: Video Configuration: x384 x400 x480 x870² x600 x624 x768 x870 x1024 built in 1MB DRAM 8 60 ns n/a 16 n/a n/a

Video in not supported at 832x624.

LOGC BOARD

Main Processor: 603e, 180 MHz PMMU: integrated FPU: integrated Data Path: 64-bit, 40 MHz

L1 Cache: 32K L2 Cache: opt'l.

Secondary Processor: opt. PC Compatbility Card

Slots: PCI, comm, TV, video in/out

NEVORY

Memory on Logic Board: 8 MB Minimum RAM: 16 MB Maximum RAM: 136 MB RAM Slots: 2 168-pin Minimum RAM Speed: 70 ns

RAM Sizes: 8, 16, 32, 64 MB

Supported Macintosh System Software:

Install in Groups of: 1

Speech Recognition Supported SOFTWARE

Addressing Modes: 32-bit ROM ID: \$077D Original SSW: 7.5.3 **ROM Version:** \$29 Original Enabler: System Enabler 410 **ROM Size: 4MB** AppleTalk Version: 58.1.5

| ☐ A/UX 1.0 | ☐ NOS 1.11 | ☐ ProDOS | |
|--------------|------------|----------------|--|
| A/UX 1.11 | ☐ NOS 1.3 | GS/OS | |
| ☐ A/UX 2.0 | ☐ NOS 2.0 | ☐ NeXTStep 1.x | |
| ☐ A/UX 3.0.1 | ☐ NOS 2.1 | ☐ NeXTStep 2.x | |
| ☐ A/UX 4.1.4 | □ LOS 7/7 | ☐ NeXTStep 3.x | |
| A/UX 4.1.4.1 | □ DOS 3.1 | ☐ OpenStep | |
| A/UX 4.1.5 | ☐ SOS 1.3 | <1.0 | |
| | | | |

SUND

⊠ Built-in Microphone

Microphone Port Type: PlainTalk Sound In: stereo, 16-bit

Sound Out: stereo, 16-bit

STORAGE

Supports ⊠ Internal CD-ROM

Floppy Size: 1.44MB Floppy Inject: manual Internal HD Size: 1.6GB Internal HD Interface: IDE Original CD-ROM Speed: 8x

HSTORY

Introduced in April 1996, the PowerMac 5400 LC looked the same as the 5200 on the outside, but inside was radically different. Running on a 120 Mhz 603e processor (a high speed variant of the 603), and initially released only to educational markets, The 5400 was the first LC to use 168-pin DIMM sockets for memory expansion. It was also the first LC to include an industry-standard PCI slot, (although it also included the familiar LC comm, video i/o, and TV slots) and the first Macintosh computer to include enhanced SRS surround sound support. The 5400 was "speed bumped" to 180/200 Mhz in February 1997, and discontinued in early 1998. It was also released in the consumer market as the Performas 5400CD, 5410CD, 5420CD, 5430CD and 5440CD, each with different hardware and software bundles. There was also a Performa 5420, which came in a black case similar to the failed Mac TV and was never released in the US.

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.