

## **Macintosh Performa 550**

#### SIEM

**VDEO** 

Introduced: October 1993 **Discontinued:** March 1995 Gestalt ID: 80 Form Factor: LC 520 Weight (lbs.): 40.5

Dimensions (inches): 17.9 H x 13.5 W x 16.5 D

Codename: Hook 33 Oder Number: M2147LL/B **KB** Article #: 15507

## **POWER**

Max. Watts: 40 **Amps:** 0.50 BTU Per Hour: 136.8 Voltage Range: 90-264 Freq'y Range (Hz): 47-63 Battery Type: 3.6V lithium

> **⊠** Soft Power **☐** Monitor Power Outlet

#### **PORIS**

**ADB**: 2 Video: none Floppy: none SCSI: DB-25 GeoPort Connectors: none

Ethernet: none Microphone Port Type: PlainTalk

> **⊠** Printer **⊠** Speaker Modem **Headphone** Remote Control ☐ Airport

Built-in Display: 14" Sony Trinitron RGB

Maximum Color Bit-depth<sup>1</sup> At:

640 640 1024 1152 1280 640 800 832 512 VRAM Speed: VRAM Needed: **Video Configuration:** x384 x400 x480 x870<sup>2</sup> x600 x624 x768 x870 x1024 built in 512K VRAM 8 80 ns n/a n/a n/a n/a n/a n/a n/a n/a 1x256K 768K VRAM n/a n/a 16 n/a n/a n/a n/a n/a n/a

### LOCCEDARD

Main Processor: 68030, 33 MHz PMMU: integrated FPU: opt. 68882 Data Path: 32-bit, 33 MHz

L1 Cache: 0.5K L2 Cache: none

Secondary Processor: none Slots: 1 LC PDS

## **NEVORY**

Memory on Logic Board: 4 MB Minimum RAM: 4 MB Maximum RAM: 36 MB RAM Slots: 1 72-pin Minimum RAM Speed: 80 ns

**RAM Sizes:** 1, 2, 4, 8, 16, 32 MB

Install in Groups of: 1

#### SOFTWARE

☐ Speech Recognition Supported

Addressing Modes: 24-, 32-bit Original SSW: 7.1P3 Original Enabler: System Enabler 332

ROM ID: \$067C ROM Version: n/a **ROM Size: 1MB** AppleTalk Version: 57.0.4

| Supported Macintosh System Software: |            |          |
|--------------------------------------|------------|----------|
| ☐ A/UX 1.0                           | ☐ NOS 1.11 | ☐ ProDOS |
| ☐ A/IIX 1 11                         | □ NOS 1 3  | GS/OS    |

A/UX 2.0 ☐ NOS 2.0 ☐ NeXTStep 1.x A/UX 3.0.1 □ NOS 2.1 ☐ NeXTStep 2.x A/UX 4.1.4 ☐ LOS 7/7 NeXTStep 3.x A/UX 4.1.4.1 ☐ DOS 3.1 OpenStep

☐ SOS 1.3

☐ A/UX 4.1.5

#### SUND Microphone Port Type: PlainTalk

Sound In: stereo, 8-bit **⊠** Built-in Microphone

Sound Out: stereo, 8-bit

# STORAGE

Supports **⊠** Internal CD-ROM

Floppy Size: 1.44MB Floppy Inject: auto **Internal HD Size: 160MB Internal HD Interface: SCSI** Original CD-ROM Speed: 4x

<1.0

# HSTORY

The LC 550 replaced the LC 520 in February 1994. It was identical to the 520, but had a 33 Mhz 68030 processor. All other specs are the same. It sold for \$1,200 and was also sold as the Performas 550, and 560.

<sup>&</sup>lt;sup>1</sup> 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

<sup>&</sup>lt;sup>2</sup> The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.