



System Fact Sheet

SYSTEM

Introduced: May 1995
Discontinued: April 1996
Gestalt ID: 99
Form Factor: LC 520
Weight (lbs.): 40.5
Dimensions (inches): 17.9 H x 13.5 W x 16.5 D

Codename:
Oder Number:
KB Article #:

POWER

Max. Watts: 40
Amps: 0.50
BTU Per Hour: 136.8
Voltage Range: 90-264
Freq'y Range (Hz): 47-63
Battery Type: 4.5V alkaline
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: opt. DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: none
Ethernet: none
Microphone Port Type: PlainTalk

Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

VIDEO **Built-in Display:** 14" RGB **Maximum Color Bit-depth¹ At:**

	512	640	640	640	800	832	1024	1152	1280
VRAM Speed:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
VRAM Needed:	60 ns	built in							
Video Configuration:	1MB DRAM								

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGICBOARD

Main Processor: 68LC040, 66 MHz
PMMU: integrated
FPU: none
Data Path: 32-bit, 33 MHz
L1 Cache: 8K
L2 Cache: none
Secondary Processor: none
Slots: LC, comm., video in/out

MEMORY

Memory on Logic Board: 4 MB
Minimum RAM: 8 MB
Maximum RAM: 52 MB
RAM Slots: 2 72-pin
Minimum RAM Speed: 80 ns
RAM Sizes: 1, 2, 4, 8, 16, 32 MB
Install in Groups of: 1

Second SIMM slot can accept only 1, 4, or 16MB SIMMs.

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 7.5
Original Enabler: none

ROM ID: \$067C
ROM Version: \$32
ROM Size: 1MB
AppleTalk Version: 58.1.3

Supported Macintosh System Software:

<input type="checkbox"/> A/UX 1.0	<input type="checkbox"/> NOS 1.11	<input type="checkbox"/> ProDOS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 1.11	<input type="checkbox"/> NOS 1.3	<input type="checkbox"/> GS/OS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 2.0	<input type="checkbox"/> NOS 2.0	<input type="checkbox"/> NeXTStep 1.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 3.0.1	<input type="checkbox"/> NOS 2.1	<input type="checkbox"/> NeXTStep 2.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4	<input type="checkbox"/> LOS 7/7	<input type="checkbox"/> NeXTStep 3.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4.1	<input type="checkbox"/> DOS 3.1	<input type="checkbox"/> OpenStep	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.5	<input type="checkbox"/> SOS 1.3	<input type="checkbox"/> <1.0	<input type="checkbox"/>

SOUND

Built-in Microphone

Microphone Port Type: PlainTalk
Sound In: mono, 8-bit
Sound Out: stereo, 8-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 500MB
Internal HD Interface: IDE
Original CD-ROM Speed: 4x

HISTORY

Released in April 1995, the LC 580 doubled the VRAM (to 1 MB) of its predecessor, the LC 575, and a video in/out slot was added. (This slot was similar to the TV tuner slot featured in the short lived Mac TV.) The LC 580 also sold as the Performas 580CD and 588CD and was discontinued a year later.