

ec Database Macintosh Performa 630CD DOS Compatible

System Fact Sheet

Q _{CIII}	л
	/

VDEO

Introduced: May 1995 Discontinued: October 1995 Gestalt ID: 98

Form Factor: Quadra 630 Weight (lbs.): 19

Dimensions (inches): 4.3 H x 12.6 W x 16.5 D

Codename: Crusader, Show Biz,

Oder Number: KB Article #:

This system is not sold in the U.S.

POWER

Max. Watts: 45 **Amps:** 1.25

BTU Per Hour: 153.9 Voltage Range: 100-240 Freq'y Range (Hz): 50-60

> Battery Type: 4.5V alkaline **⊠** Soft Power

> > **☐** Monitor Power Outlet

PORIS

ADB: 1 Video: DB-15 Floppy: none

SCSI: DB-25

GeoPort Connectors: none

Ethernet: none

Microphone Port Type: PlainTalk

⊠ Printer **⊠** Speaker

Modem **Headphone** ☐ Airport **⊠** Remote Control

PC game port also available.

800

Built-in Display: none VRAM Speed: VRAM Needed:

built in

Video Configuration: 1MB DRAM

640 512 x384 x400 16 n/a

x480 16

640 x870² n/a

x600 x624 8

Maximum Color Bit-depth¹ At:

832 1024 1152 1280 x768 x870 x1024 n/a

n/a n/a

Video in not supported at 832x624.

60 ns

LOGOBOARD

Main Processor: 68LC040, 66 MHz PMMU: integrated FPU: none

Data Path: 32-bit, 33 MHz L1 Cache: 8K L2 Cache: none

Secondary Processor: 486DX2, 66 MHz

Slots: Comm., TV, video in

NEVORY

Memory on Logic Board: 4 MB

Minimum RAM: 8 MB Maximum RAM: 52 MB RAM Slots: 2 72-pin

Minimum RAM Speed: 80 ns

RAM Sizes: 1, 2, 4, 8, 16, 32 MB

Install in Groups of: 1

Second SIMM slot can accept only 1, 4, or 16MB SIMMs. DOS card can accept one 72-pin SIMM (Š 80 ns), up to 32MB in size -- comes with 4MB SIMM installed.

SOFTWARE

☐ Speech Recognition Supported

Sound Out: stereo, 8-bit

Addressing Modes: 32-bit Original SSW: 7.5.1 Original Enabler: none

ROM ID: \$067C ROM Version: \$32 **ROM Size: 1MB**

AppleTalk Version: 58.1.3

Supported Macintosh System Software:

☐ A/UX 1.0 ☐ NOS 1.11 ☐ ProDOS GS/OS ☐ NOS 1.3 A/UX 1.11 ☐ NOS 2.0 NeXTStep 1.x A/UX 2.0 NeXTStep 2.x A/UX 3.0.1 □ NOS 2.1

A/UX 4.1.4 LOS 7/7 A/UX 4.1.4.1 DOS 3.1 ☐ A/UX 4.1.5

NeXTStep 3.x OpenStep ☐ SOS 1.3 <1.0

Includes Microsoft MS-DOS 6.22 and Windows 3.1.

SUND

Microphone Port Type: PlainTalk Sound In: mono, 8-bit Built-in Microphone

Comes with Sound Blaster 16-compatible expansion card.

STORAGE

Supports **⊠** Internal CD-ROM

Floppy Size: 1.44MB Floppy Inject: manual **Internal HD Size: 500MB** Internal HD Interface: IDE Original CD-ROM Speed: 2x

HSTORY

The last of the Quadra line, the Quadra 630 was introduced in June 1994. The 630 was a hybrid of a Quadra and an LC in a sleek new case. It had an internal IDE hard drive (the 630 was the first Mac to use the IDE bus), and an optional CD-ROM drive. It sold for \$1,200, and was also released as the LC 630, and the Performa 630, 630CD, 631CD, 635CD, 636, 636CD, 637CD, 638CD, and 640CD, each of which was bundled with different software, accessories, monitors, and hard drives (some Performas had a 68LC040, and several were also available with a 25 Mhz 486SX DOS card). The Quadra 630 was discontinued in August 1995.

Note: n/a = information not available or not applicable

Database Last Modified On: 1/7/2003

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.