

# Macintosh Performa 6320CD

## SIEW

Introduced: April 1996 Discontinued: June 1997 Gestalt ID: 42 Form Factor: Quadra 630

Weight (lbs.): 19

**Dimensions (inches):** 4.3 H x 12.6 W x 16.5 D

Codename: Crusader Oder Number: M4957LL/A KB Article #: 19594, 19595

## **POWER**

Max. Watts: 55 **Amps:** 1.25 BTU Per Hour: 188.1 Voltage Range: 110-240 Freq'y Range (Hz): 50-60

Battery Type: 4.5V alkaline

**⊠** Soft Power

**☐** Monitor Power Outlet

## **PORIS**

**ADB:** 1 Video: DB-15 Floppy: none SCSI: DB-25

GeoPort Connectors: none

Ethernet: none

Microphone Port Type: PlainTalk

**⊠** Printer

**⊠** Speaker

Modem ☐ Airport **Headphone ⊠** Remote Control

**VDEO** 

Built-in Display: none

VRAM Speed: VRAM Needed:

built in

Video Configuration:

640 512 x384 x400 n/a

x480 16

640 x870<sup>2</sup> x600 n/a

x624 8

Maximum Color Bit-depth<sup>1</sup> At:

800

832 1024 1152 1280 x768 x870 x1024 n/a

n/a n/a

<sup>1</sup> 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

1MB DRAM

<sup>2</sup> The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

Video in not supported at 832x624.

60 ns

#### LOGC BOARD

Main Processor: 603e, 120 MHz PMMU: integrated FPU: integrated Data Path: 64-bit, 40 MHz

L1 Cache: 32K L2 Cache: 256K Secondary Processor: none

Slots: LC, comm, TV, video in/out

#### **NEVORY**

Memory on Logic Board: none Minimum RAM: 16 MB Maximum RAM: 64 MB RAM Slots: 2 72-pin Minimum RAM Speed: 80 ns

**RAM Sizes:** 4, 8, 16, 32 MB

Install in Groups of: 1

#### SOFTWARE

Speech Recognition Supported

Sound Out: stereo, 16-bit

Addressing Modes: 32-bit Original SSW: 7.5.1

Original Enabler: System Enabler 406

**ROM ID: \$077D** ROM Version: n/a

**ROM Size:** 4MB AppleTalk Version: 58.1.3

Sup	por	ted	Mac	cintos	h S	ys	tem	Soi	twar	e:

☐ ProDOS ☐ A/UX 1.0 NOS 1.11 A/UX 1.11 GS/OS NOS 1.3 ☐ NOS 2.0 NeXTStep 1.x A/UX 2.0 ☐ A/UX 3.0.1 NeXTStep 2.x □ NOS 2.1 A/UX 4.1.4 LOS 7/7 NeXTStep 3.x A/UX 4.1.4.1

☐ A/UX 4.1.5

☐ DOS 3.1 ☐ SOS 1.3

OpenStep <1.0

#### SUND

Microphone Port Type: PlainTalk Sound In: mono, 16-bit Built-in Microphone

INPUT: impedance 100 kOhm; avg. line level 100 mV rms; avg. mic. level 70 mV rms, max. input level 1.8 V rms

## STORAGE

Supports **⊠** Internal CD-ROM

Floppy Size: 1.44MB Floppy Inject: manual Internal HD Size: 1.2GB Internal HD Interface: IDE Original CD-ROM Speed: 4x

# HSTORY

The PowerMac 6200 was a 5200 in a Quadra 630-style case. The 6200 was sold only in Europe, but was released in the US as the Performas 6200CD, 6205CD, 6210CD, 6214CD, 6216CD, 6218CD, 6220CD, and 6230CD, each bundled with a 15" monitor, and a different hard drive. In late 1995 and early 1996, apple released several more machines based on the same motherboard, with similar specs: The Performas 6260CD, 6290CD, 6300CD, and 6310CD each ran on a 100 Mhz 603e, and the PowerMac 6300/120 and the Performa 6320 each ran on a 120 Mhz 603e. They were all eventually replaced by the Performa 6360.