

Macintosh PowerBook 1400cs/166

System Fact Sheet SIEM

Introduced: October 1997 Discontinued: n/a

Gestalt ID: 310 Form Factor: PowerBook 1400

Weight (lbs.): 6.6 Dimensions (inches): 2 H x 11.5 W x 9 D

> Codename: Epic Oder Number: **KB Article #: 20468**

Weight of this machine varies depending on

accessories installed

POWER

Max. Watts: 45 **Amps:** 1.875

BTU Per Hour: 153.9 Voltage Range: 100-220 Freq'y Range (Hz): 50-60

Battery Type: PB1400, NiMH

⊠ Soft Power

☐ Monitor Power Outlet

пв	12

ADB: 1

Video: opt. mini-15

Floppy: none SCSI: HDI-30

GeoPort Connectors: none

Ethernet: none

Microphone Port Type: Line In

⊠ Printer **⊠** Speaker

Headphone

Modem ☐ Airport

Remote Control

na/

VDEO

Built-in Display: 11.3" active matrix LCD

Maximum Color Bit-depth¹ At:

640 1024 1152 1280 800 832 x768

VRAM Speed: VRAM Needed: built in n/a

Video Configuration: built-in LCD screen

640 x384 x400 n/a

512

x480 x870² x600 x624 n/a n/a 16 n/a

x870 x1024 n/a n/a

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions ² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGOBOARD

Main Processor: 603e, 166MHz PMMU: integrated

> FPU: integrated Data Path: 64-bit, 33.3MHz

L1 Cache: 32K L2 Cache: 128K Secondary Processor: none

Slots: 2 Type II PC Card (1 Type III)

NEVORY

Memory on Logic Board: 16 MB

Minimum RAM: 16 MB

Maximum RAM: 64 MB

RAM Slots: 1 PB1400 Minimum RAM Speed: 70 ns

RAM Sizes: 8-24 MB

Install in Groups of: 1

Memory expansion slot allows "piggy backing" of up to two memory

SOFIWARE

Addressing Modes: 32-bit Original SSW: 8.0 Original Enabler: none

Speech Recognition Supported

ROM ID: \$077D ROM Version: n/a **ROM Size: 4MB**

AppleTalk Version: n/a

Supported Macintosh System Software:

☐ ProDOS A/UX 1.0 ☐ NOS 1.11 GS/OS A/UX 1.11 ☐ NOS 1.3 ☐ NOS 2.0 NeXTStep 1.x A/UX 2.0

NeXTStep 2.x A/UX 3.0.1 □ NOS 2.1 A/UX 4.1.4 LOS 7/7 NeXTStep 3.x

A/UX 4.1.4.1 DOS 3.1 OpenStep

☐ A/UX 4.1.5 ☐ SOS 1.3 <1.0

SUND

⊠ Built-in Microphone

Microphone Port Type: Line In

Sound In: mono, 16-bit Sound Out: stereo, 16-bit STORAGE

Supports **⊠** Internal CD-ROM

Floppy Size: 1.44MB Floppy Inject: manual Internal HD Size: 1.3GB **Internal HD Interface: ATA** Original CD-ROM Speed: 8x

HSTORY

Announced in October 1996, The PowerBook 1400 was a partial answer to a number of questions about recent PowerBooks. Powered by the same 117 Mhz 603e as the 5300, the 1400 was the first PowerBook to include an internal CD-ROM drive (6X). The bay for the sleep-swapable drive could also accomidate a variety of other storage options, including MO and zip drives. The RAM came in stackable modules (another PowerBook 1st) allowing for up to 64 MB of RAM. The 1400 also included an Internal expansion slot for video-out or Ethernet cards, and two PC Card slots that could accommodate two Type II PC Cards or one Type III PC Card. Faster models with a small L2 cache and an 8x CD-ROM drive were also released. The 1400 was discontinued early in 1998.