



System Fact Sheet

SYSTEM

Introduced: August 1997
Discontinued: October 1997
Gestalt ID: 108
Form Factor: Power Computing
Weight (lbs.): 21
Dimensions (inches): 4.4 H x 16.8 W x 16 D

Codename:
Order Number:
KB Article #: 36297

POWER

Max. Watts: 145
Amps:
BTU Per Hour: 495.9
Voltage Range: 100-240 V
Freq'y Range (Hz): 50-60 Hz
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: 2
Ethernet: AAUI-15 &
Microphone Port Type: PlainTalk
 Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

VIDEO

Built-in Display: *Maximum Color Bit-depth¹ At:*

	512	640	640	640	800	832	1024	1152	1280
VRAM Speed:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
VRAM Needed:									8
VRAM									
Video Configuration:									
									1,2,4MB

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

ATI Rage II

LOGICBOARD

Main Processor: 604e, 240 MHz
PMMU: none
FPU: none
Data Path: , 60 MHz
L1 Cache: 32K
L2 Cache: 1MB
Secondary Processor: none
Slots: 3 PCI

1 PCI slot is used for the Adaptec Ultra SCSI card

MEMORY

Memory on Logic Board: 16MB
Minimum RAM: 16MB
Maximum RAM: 512MB
RAM Slots: 4 168-pin
Minimum RAM Speed: 60 ns
RAM Sizes: 32, 64, 128 MB
Install in Groups of: 1

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 7.5.3
Original Enabler:

ROM ID:
ROM Version:
ROM Size: 4MB
AppleTalk Version:

SUPPORTED MACINTOSH SYSTEM SOFTWARE:

<input type="checkbox"/> A/UX 1.0	<input type="checkbox"/> NOS 1.11	<input type="checkbox"/> ProDOS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 1.11	<input type="checkbox"/> NOS 1.3	<input type="checkbox"/> GS/OS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 2.0	<input type="checkbox"/> NOS 2.0	<input type="checkbox"/> NeXTStep 1.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 3.0.1	<input type="checkbox"/> NOS 2.1	<input type="checkbox"/> NeXTStep 2.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4	<input type="checkbox"/> LOS 7/7	<input type="checkbox"/> NeXTStep 3.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4.1	<input type="checkbox"/> DOS 3.1	<input type="checkbox"/> OpenStep	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.5	<input type="checkbox"/> SOS 1.3	<input type="checkbox"/> <1.0	<input type="checkbox"/>

SOUND

Built-in Microphone

Microphone Port Type: PlainTalk
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 2GB
Internal HD Interface: SCSI
Original CD-ROM Speed: 16x

HISTORY

The PowerCenter Pro was available in desktop and tower configurations, with speed ranging from 180-240 MHz using the PPC 604e processor. The CPU was on a daughtercard for ease of upgrade. These computers had a 60 MHz bus speed which made them faster than comparable machines at the time.

Bundled software: MacOS 8, FWB Hard Disk Toolkit 2.0, FWB CD-ROM Toolkit 2.0, Adobe Acrobat Reader 3.0, ClarisWorks 4.0, Corel Gallery Clip Art, Fractal Dabblers 2.0, Asante Net Doubler, Now Up-to-Date/Contact, Blockbuster Guide to Movies and Videos (CD-ROM), 250 Bitstream fonts; Trial versions of AOL, CompuServer, Nisus software