



System Fact Sheet

SYSTEM

Introduced: July 1996
Discontinued: October 1997
Gestalt ID: 67
Form Factor: Power Computing
Weight (lbs.): 27
Dimensions (inches): 16.9 H x 7.7 W x 17.3 D

Codename:
Oder Number:
KB Article #: 36163

POWER

Max. Watts: 300
Amps:
BTU Per Hour: 1026
Voltage Range: 100-240 V
Freq'y Range (Hz): 50-60 Hz
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: 2
Ethernet: AAUI-15 &
Microphone Port Type: PlainTalk
 Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

*1 PS/2 mouse port
1 PS/2 keyboard port*

VIDEO

Built-in Display: *Maximum Color Bit-depth¹ At:*

	512	640	640	640	800	832	1024	1152	1280
VRAM Speed:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
VRAM Needed:									
VRAM									8
Video Configuration:									
									4,8MB

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

ixMicro TwinTurbo

LOGICBOARD

Main Processor: 604e, 225 MHz
PMMU: none
FPU: none
Data Path: , 51.4 MHz
L1 Cache: 32K
L2 Cache: 1MB
Secondary Processor: none
Slots: 6 PCI

MEMORY

Memory on Logic Board: 16MB
Minimum RAM: 16MB
Maximum RAM: 1GB
RAM Slots: 8 168-pin
Minimum RAM Speed: 70 ns
RAM Sizes: 32, 64, 128 MB
Install in Groups of: 1

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 7.5.3
Original Enabler:

ROM ID:
ROM Version:
ROM Size: 4MB
AppleTalk Version:

Supported Macintosh System Software:

<input type="checkbox"/> A/UX 1.0	<input type="checkbox"/> NOS 1.11	<input type="checkbox"/> ProDOS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 1.11	<input type="checkbox"/> NOS 1.3	<input type="checkbox"/> GS/OS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 2.0	<input type="checkbox"/> NOS 2.0	<input type="checkbox"/> NeXTStep 1.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 3.0.1	<input type="checkbox"/> NOS 2.1	<input type="checkbox"/> NeXTStep 2.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4	<input type="checkbox"/> LOS 7/7	<input type="checkbox"/> NeXTStep 3.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4.1	<input type="checkbox"/> DOS 3.1	<input type="checkbox"/> OpenStep	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.5	<input type="checkbox"/> SOS 1.3	<input type="checkbox"/> <1.0	<input type="checkbox"/>

SOUND

Built-in Microphone

Microphone Port Type: PlainTalk
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 2GB
Internal HD Interface: SCSI
Original CD-ROM Speed: 8x

HISTORY

The PowerTower Pro came in a tower configuration with speed ranging from 180 to 250 MHz using the PPC 604e processor. The CPU was on a daughter card for ease of upgrade. This is the first PC on any platform to ship at 225Mhz and its technology is dual processor capable.