



System Fact Sheet

SYSTEM

Introduced: November 1994
Discontinued: March 1996
Gestalt ID: 104
Form Factor: LC
Weight (lbs.): 8.8
Dimensions (inches): 2.9 H x 12.2 W x 15.3 D

Codename:
Order Number:
KB Article #:

POWER

Max. Watts: 30
Amps: 0.25
BTU Per Hour: 102.6
Voltage Range: 100-240
Freq'y Range (Hz): 47-63
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: none
Ethernet: none
Microphone Port Type: PlainTalk

Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

VIDEO **Built-in Display:** none

| | | <i>Maximum Color Bit-depth¹ At:</i> | | | | | | | | | |
|--------------------|---------------------|--|------|------|-------------------|------|------|------|------|-------|--|
| | | 512 | 640 | 640 | 640 | 800 | 832 | 1024 | 1152 | 1280 | |
| VRAM Speed: | VRAM Needed: | x384 | x400 | x480 | x870 ² | x600 | x624 | x768 | x870 | x1024 | |
| 80 ns | 2x256K | 16 | n/a | 8 | 4 | n/a | 8 | 4 | 4 | n/a | |
| | 2x512K | 16 | n/a | 16 | 8 | n/a | 16 | 8 | 8 | n/a | |

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGICBOARD

Main Processor: 601, 50 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 25 MHz
L1 Cache: 32K
L2 Cache: 256K
Secondary Processor: 68LC040, 50 MHz
Slots: LC PDS (unavailable)

This configuration is achieved by installing the Macintosh Processor Upgrade Card.

MEMORY

Memory on Logic Board: 4 MB
Minimum RAM: 4 MB
Maximum RAM: 36 MB
RAM Slots: 1 72-pin
Minimum RAM Speed: 80 ns
RAM Sizes: 1, 2, 4, 8, 16, 32 MB
Install in Groups of: 1

SOFTWARE **Speech Recognition Supported**

Addressing Modes: 32-bit
Original SSW: 7.5
Original Enabler: 601 Processor Upgrade Enabler

ROM ID: \$077D
ROM Version: n/a
ROM Size: 4MB
AppleTalk Version: n/a

Supported Macintosh System Software:

| | | | |
|---------------------------------------|-----------------------------------|---------------------------------------|--------------------------|
| <input type="checkbox"/> A/UX 1.0 | <input type="checkbox"/> NOS 1.11 | <input type="checkbox"/> ProDOS | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 1.11 | <input type="checkbox"/> NOS 1.3 | <input type="checkbox"/> GS/OS | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 2.0 | <input type="checkbox"/> NOS 2.0 | <input type="checkbox"/> NeXTStep 1.x | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 3.0.1 | <input type="checkbox"/> NOS 2.1 | <input type="checkbox"/> NeXTStep 2.x | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 4.1.4 | <input type="checkbox"/> LOS 7/7 | <input type="checkbox"/> NeXTStep 3.x | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 4.1.4.1 | <input type="checkbox"/> DOS 3.1 | <input type="checkbox"/> OpenStep | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 4.1.5 | <input type="checkbox"/> SOS 1.3 | <input type="checkbox"/> <1.0 | <input type="checkbox"/> |

SOUND

Built-in Microphone

Microphone Port Type: PlainTalk
Sound In: mono, 8-bit
Sound Out: stereo, 8-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 80-250MB
Internal HD Interface: SCSI
Original CD-ROM Speed:

HISTORY