

Power Macintosh 6300/120

SIEM

VDEO

Introduced: June 1996 Discontinued: June 1997 Gestalt ID: 42 Form Factor: Quadra 630

Weight (lbs.): 19

Dimensions (inches): 4.3 H x 12.6 W x 16.5 D

Codename: Crusader Oder Number: KB Article #:

This system is not sold in the U.S.

POWER

Max. Watts: 55 Amps: 1.25 BTU Per Hour: 188.1 Voltage Range: 110-240

Freq'y Range (Hz): 50-60 Battery Type: 4.5V alkaline

⊠ Soft Power

Monitor Power Outlet

PORIS

ADB: 1 Video: DB-15 Floppy: none SCSI: DB-25

GeoPort Connectors: none

Ethernet: none

Microphone Port Type: PlainTalk

Modem Headphone

| Modem | Reauphone | |
| Airport | | Remote Control

Built-in Display: none

Maximum Color Bit-depth¹ At:

640 640 640 800 832 1024 1152 1280 400 x480 x870² x600 x624 x768 x870 x1024

VRAM Speed: VRAM Needed: 60 ns built in

Video Configuration: 1MB DRAM 512 640 x384 x400 n/a n/a

x480 x870² 16 n/a

624 x / 68 x 8 / / 8 n/a n/a

n/a n/a

Video in not supported at 832x624.

LOGOBOARD

Main Processor: 603e, 120 MHz PMMU: integrated FPU: integrated Data Path: 64-bit, 40 MHz

L1 Cache: 32K L2 Cache: 256K Secondary Processor: none

Slots: LC, comm, TV, video in/out

Mevory

Memory on Logic Board: none
Minimum RAM: 16 MB
Maximum RAM: 64 MB
RAM Slots: 2 72-pin
Minimum RAM Speed: 80 ns

RAM Sizes: 4, 8, 16, 32 MB

Install in Groups of: 1

SOFTWARE

Speech Recognition Supported

Sound In: mono, 16-bit

Sound Out: stereo, 16-bit

Microphone Port Type: PlainTalk

Addressing Modes: 32-bit Original SSW: 7.5.1

Original Enabler: System Enabler 406

ROM ID: \$077D ROM Version: n/a

ROM Size: 4MB **AppleTalk Version:** 58.1.3

Supported	Macintosh	System	Software:

		☐ ProDOS	
☐ A/UX 1.11	☐ NOS 1.3	☐ GS/OS	
☐ A/UX 2.0	☐ NOS 2.0	☐ NeXTStep 1.x	
☐ A/UX 3.0.1	☐ NOS 2.1	☐ NeXTStep 2.x	
☐ A/UX 4.1.4	☐ LOS 7/7	☐ NeXTStep 3.x	
A/UX 4.1.4.1	☐ DOS 3.1	OpenStep	

☐ SOS 1.3

☐ A/UX 4.1.5

STORAGE

Supports
Internal
CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 1.2GB
Internal HD Interface: IDE
Original CD-ROM Speed: 4x

<1.0

SUND

Built-in Microphone

INPUT: impedance 100 kOhm; avg. line level 100 mV rms; avg. mic. level 70 mV rms, max. input level 1.8 V rms

HSTORY

The PowerMac 6200 was a 5200 in a Quadra 630-style case. The 6200 was sold only in Europe, but was released in the US as the Performas 6200CD, 6205CD, 6210CD, 6214CD, 6216CD, 6218CD, 6220CD, and 6230CD, each bundled with a 15" monitor, and a different hard drive. In late 1995 and early 1996, apple released several more machines based on the same motherboard, with similar specs: The Performas 6260CD, 6290CD, 6300CD, and 6310CD each ran on a 100 Mhz 603e, and the PowerMac 6300/120 and the Performa 6320 each ran on a 120 Mhz 603e. They were all eventually replaced by the Performa 6360.

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.