

# Power Macintosh 8100/110

# SIEM

**VDEO** 

Introduced: November 1994 Discontinued: August 1995 Gestalt ID: 40 Form Factor: Quadra 800 Weight (lbs.): 25.3

**Dimensions (inches):** 14 H x 7.7 W x 15.75 D

Codename: Flagship Oder Number:

KB Article #: 16932, 16661

### POWER

Max. Watts: 200 Amps: 9.00 BTU Per Hour: 684 Voltage Range: 100-240 Freq'y Range (Hz): 50-60 Battery Type: 3.6V lithium

**⊠** Soft Power

Monitor Power Outlet

### **PORIS**

**ADB:** 1

Video: DB-15 & HDI-45

Floppy: none SCSI: DB-25

**GeoPort Connectors: 2** 

Ethernet: AAUI-15

Microphone Port Type: PlainTalk

Maximum Color Bit-depth<sup>1</sup> At:

**Modem** ☐ Headphone

Airport Remote Control

Built-in	Display:	none	

VRAM Speed: VRAM Needed:	Video Configuration:	512 x384	640 x400	640 x480	640 x870 <sup>2</sup>	800 x600	832 x624	1024 x768	1152 x870	1280 x1024
80 ns built in	DRAM (HDI-45)	16	n/a	16	8	n/a	8	n/a	n/a	n/a
built in	2MB VRAM	24	n/a	24	8	n/a	24	16	16	n/a
4x512K	4MB VRAM	24	n/a	24	8	n/a	24	24	24	n/a

<sup>&</sup>lt;sup>1</sup> 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

### LOGC BOAFD

Main Processor: 601+, 110 MHz PMMU: integrated FPU: integrated Data Path: 64-bit, 36.7 MHz

L1 Cache: 32K L2 Cache: 256K Secondary Processor: none

Slots: 3 NuBus, PDS filled

### **NEVORY**

Memory on Logic Board: 8 MB
Minimum RAM: 16 MB
Maximum RAM: 264 MB
RAM Slots: 8 72-pin
Minimum RAM Speed: 80 ns

**RAM Sizes:** 4, 8, 16, 32 MB

**Install in Groups of:** 2

☐ A/UX 4.1.5

### SOFTWARE

#### Speech Recognition Supported

Addressing Modes: 32-bit ROM ID: \$077D Original SSW: 7.5 ROM Version: \$23 Original Enabler: PowerPC Enabler v1.1.1 ROM Size: 4MB AppleTalk Version: 58.1.3

Supported Macintosh System Software:					
☐ A/UX 1.0	☐ NOS 1.11	☐ ProDOS			
☐ A/IIV 1 11	□ NOS 1 3	CS/OS			

 A/UX 1.11
 NOS 1.3
 □ GS/OS
 □

 A/UX 2.0
 NOS 2.0
 NeXTStep 1.x
 □

 A/UX 3.0.1
 NOS 2.1
 NeXTStep 2.x
 □

 A/UX 4.1.4
 □ LOS 7/7
 □ NeXTStep 3.x
 □

 A/UX 4.1.4.1
 □ DOS 3.1
 □ OpenStep
 □

☐ SOS 1.3

#### **SIND**

Microphone Port Type: PlainTalk

Sound In: stereo, 16-bit

Built-in Microphone Sound Out: stereo, 16-bit

# STORAGE

Supports
Internal
CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 2GB
Internal HD Interface: SCSI
Original CD-ROM Speed: 2x

<1.0

### HSICRY

Introduced in March of 1994, the PowerMac 8100 was the fastest, most expandable first-generation PowerMac. It shipped in a Quadra 800-style case, and was speed bumped to 100 Mhz in November, and to 110 Mhz in January 1995. It was originally priced at \$4,250.

<sup>&</sup>lt;sup>2</sup> The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.