



System Fact Sheet

SYSTEM

Introduced: October 1993
Discontinued: October 1994
Gestalt ID: 94
Form Factor: LC
Weight (lbs.): 8.8
Dimensions (inches): 2.9 H x 12.2 W x 15.3 D

Codename: Aladdin, Primus
Oder Number: M1821LL/A
KB Article #: 13595

POWER

Max. Watts: 30
Amps: 0.44
BTU Per Hour: 102.6
Voltage Range: 100-240
Freq'y Range (Hz): 47-63
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: none
Ethernet: none
Microphone Port Type: PlainTalk
 Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

VIDEO

Built-in Display: none

Maximum Color Bit-depth¹ At:

| VRAM Speed: | VRAM Needed: | Video Configuration: | 512 | 640 | 640 | 640 | 800 | 832 | 1024 | 1152 | 1280 |
|-------------|--------------|----------------------|------|------|------|-------------------|------|------|------|------|-------|
| 80 ns | 2x256K | 512K VRAM | x384 | x400 | x480 | x870 ² | x600 | x624 | x768 | x870 | x1024 |
| | 2x512K | 1MB VRAM | 16 | n/a | 8 | 4 | n/a | 8 | 4 | 4 | n/a |
| | | | 16 | n/a | 16 | 8 | n/a | 16 | 8 | 8 | n/a |

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGIC BOARD

Main Processor: 68LC040, 25 MHz
PMMU: integrated
FPU: none
Data Path: 32-bit, 25 MHz
L1 Cache: 8K
L2 Cache: none
Secondary Processor: none
Slots: 1 LC III PDS

MEMORY

Memory on Logic Board: 4 MB
Minimum RAM: 4 MB
Maximum RAM: 36 MB
RAM Slots: 1 72-pin
Minimum RAM Speed: 80 ns
RAM Sizes: 1, 2, 4, 8, 16, 32 MB
Install in Groups of: 1

SOFTWARE

Speech Recognition Supported

Addressing Modes: 24-, 32-bit
Original SSW: 7.1
Original Enabler: System Enabler 065

ROM ID: \$067C
ROM Version: n/a
ROM Size: 512k*
AppleTalk Version: 57.0.4

Supported Macintosh System Software:

- A/UX 1.0 NOS 1.11 ProDOS
- A/UX 1.11 NOS 1.3 GS/OS
- A/UX 2.0 NOS 2.0 NeXTStep 1.x
- A/UX 3.0.1 NOS 2.1 NeXTStep 2.x
- A/UX 4.1.4 LOS 7/7 NeXTStep 3.x
- A/UX 4.1.4.1 DOS 3.1 OpenStep
- A/UX 4.1.5 SOS 1.3 <1.0

ROM = 512k: expandable to 1MB

SOUND

Microphone Port Type: PlainTalk
Sound In: mono, 8-bit
Sound Out: stereo, 8-bit

Built-in Microphone

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 80-160MB
Internal HD Interface: SCSI
Original CD-ROM Speed:

HISTORY

The most affordable Quadra ever, the 605 was released in October 1993. It had a 25 MHz 68LC040 processor, and came in a small newly designed case. It sold for \$900 and was discontinued in October 1994. It was also sold as the LC 475, and as Performas 475 and 476 which were bundled with various combinations of a fax/modems, monitors, and hard drives.