



System Fact Sheet

SYSTEM

Introduced: February 1996
Discontinued: April 1997
Gestalt ID: 108
Form Factor: PM 7500
Weight (lbs.): 22
Dimensions (inches): 6.15 H x 14.37 W x 16.93 D
Codename: Summit
Oder Number: M4335LL/A
KB Article #: 19163, 19164

POWER

Max. Watts: 150
Amps: 3.00
BTU Per Hour: 513
Voltage Range: 100-270
Freq'y Range (Hz): 50-60
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: 2
Ethernet: AAUI-15 &
Microphone Port Type: PlainTalk
 Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

VIDEO

Built-in Display: none

Maximum Color Bit-depth¹ At:

VRAM Speed:	VRAM Needed:	Video Configuration:	512	640	640	640	800	832	1024	1152	1280
70 ns	built in	1MB VRAM	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
	1x1MB	2MB VRAM	24	n/a	16	8	16	16	8	8	n/a
	3x1MB	4MB VRAM	24	n/a	24	8	24	24	16	16	8
			24	n/a	24	8	24	24	24	24	16

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGIC BOARD

Main Processor: 601, 120 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 40 MHz
L1 Cache: 32K
L2 Cache: 256K
Secondary Processor: none
Slots: 3 PCI

MEMORY

Memory on Logic Board: none
Minimum RAM: 16 MB
Maximum RAM: 256 MB
RAM Slots: 4 168-pin
Minimum RAM Speed: 70 ns
RAM Sizes: 8, 16, 32, 64 MB
Install in Groups of: 1

128MB DIMMs can be used, but have not been tested.

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 7.5.3
Original Enabler: none

ROM ID: \$077D
ROM Version: n/a
ROM Size: 4MB
AppleTalk Version: 60.1.0

Supported Macintosh System Software:

- | | | | |
|---------------------------------------|-----------------------------------|---------------------------------------|--------------------------|
| <input type="checkbox"/> A/UX 1.0 | <input type="checkbox"/> NOS 1.11 | <input type="checkbox"/> ProDOS | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 1.11 | <input type="checkbox"/> NOS 1.3 | <input type="checkbox"/> GS/OS | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 2.0 | <input type="checkbox"/> NOS 2.0 | <input type="checkbox"/> NeXTStep 1.x | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 3.0.1 | <input type="checkbox"/> NOS 2.1 | <input type="checkbox"/> NeXTStep 2.x | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 4.1.4 | <input type="checkbox"/> LOS 7/7 | <input type="checkbox"/> NeXTStep 3.x | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 4.1.4.1 | <input type="checkbox"/> DOS 3.1 | <input type="checkbox"/> OpenStep | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 4.1.5 | <input type="checkbox"/> SOS 1.3 | <input type="checkbox"/> <1.0 | <input type="checkbox"/> |

SOUND

Microphone Port Type: PlainTalk
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

Built-in Microphone

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 1.2-2GB
Internal HD Interface: SCSI
Original CD-ROM Speed: 8x

HISTORY

The Workgroup Server 7250 was based on the motherboard of the PowerMac 7200, and included bundled server software.

The 2 GB, 4500-rpm hard disk drive and 8x-speed CD-ROM drive are available in models M5482LL/A, M5483LL/A, and M5484LL/A; not in the earlier configurations.