



System Fact Sheet

SYSTEM

Introduced: September 1996
Discontinued: April 1997
Gestalt ID: 69
Form Factor: Quadra 800
Weight (lbs.): 25
Dimensions (inches): 14 H x 7.7 W x 15.75 D

Codename: Summit
Oder Number: M5486LL/A
KB Article #: 20371, 20372

POWER

Max. Watts: 225
Amps: 9.00
BTU Per Hour: 769.5
Voltage Range: 100-240
Freq'y Range (Hz): 50-60
Battery Type: 3.6V lithium

Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15
Floppy: none
SCSI: DB-25

GeoPort Connectors: 2
Ethernet: AAUI-15 &

Microphone Port Type: PlainTalk

Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

VIDEO **Built-in Display:** none

		<i>Maximum Color Bit-depth¹ At:</i>									
		512	640	640	640	800	832	1024	1152	1280	
VRAM Speed:	VRAM Needed:	Video Configuration:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
70 ns	2x1MB	2MB VRAM	24	n/a	24	8	24	24	16	16	8
	4x1MB	4MB VRAM	24	n/a	24	8	24	24	24	24	16

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGICBOARD

Main Processor: 604e, 200 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 50 MHz
L1 Cache: 64K
L2 Cache: 512K

Secondary Processor: none
Slots: 3 PCI

MEMORY

Memory on Logic Board: none
Minimum RAM: 32 MB
Maximum RAM: 512 MB
RAM Slots: 8 168-pin
Minimum RAM Speed: 70 ns
RAM Sizes: 8, 16, 32, 64 MB
Install in Groups of: 1

128MB DIMMs can be used, but have not been tested.

SOFTWARE **Speech Recognition Supported**

Addressing Modes: 32-bit
Original SSW: 7.5.3
Original Enabler: none

ROM ID: \$077D
ROM Version: n/a
ROM Size: 4MB
AppleTalk Version: 60.1.0

Supported Macintosh System Software:

<input type="checkbox"/> A/UX 1.0	<input type="checkbox"/> NOS 1.11	<input type="checkbox"/> ProDOS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 1.11	<input type="checkbox"/> NOS 1.3	<input type="checkbox"/> GS/OS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 2.0	<input type="checkbox"/> NOS 2.0	<input type="checkbox"/> NeXTStep 1.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 3.0.1	<input type="checkbox"/> NOS 2.1	<input type="checkbox"/> NeXTStep 2.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4	<input type="checkbox"/> LOS 7/7	<input type="checkbox"/> NeXTStep 3.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4.1	<input type="checkbox"/> DOS 3.1	<input type="checkbox"/> OpenStep	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.5	<input type="checkbox"/> SOS 1.3	<input type="checkbox"/> <1.0	<input type="checkbox"/>

SOUND

Built-in Microphone

Microphone Port Type: PlainTalk
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 2GB
Internal HD Interface: SCSI
Original CD-ROM Speed: 8x

HISTORY

The Workgroup Server 8550 was based on the motherboard of the PowerMac 8500, and included bundled server software. It was "speed bumped" to a 200 Mhz 604e in September 1996.