



System Fact Sheet

SYSTEM

Introduced: April 1994
Discontinued: April 1995
Gestalt ID: 39
Form Factor: WS 9150
Weight (lbs.): 36.8
Dimensions (inches): 18.6 H x 8.9 W x 20.6 D

Codename: Green Giant
Oder Number:
KB Article #: 15211

POWER

Max. Watts: 303
Amps: 10.00
BTU Per Hour: 1036.26
Voltage Range: 100-240
Freq'y Range (Hz): 50-60
Battery Type: 3.6V lithium

Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: 2
Ethernet: AAUI-15

Microphone Port Type: Omni

Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

VIDEO

Built-in Display: none

VRAM Speed: n/a **VRAM Needed:** built in **Video Configuration:** DRAM

| | | <i>Maximum Color Bit-depth¹ At:</i> | | | | | | | | | |
|--------------------|---------------------|--|------|------|-------------------|------|------|------|------|-------|--|
| | | 512 | 640 | 640 | 640 | 800 | 832 | 1024 | 1152 | 1280 | |
| VRAM Speed: | VRAM Needed: | x384 | x400 | x480 | x870 ² | x600 | x624 | x768 | x870 | x1024 | |
| | | 16 | n/a | 16 | 8 | n/a | 8 | n/a | n/a | n/a | |

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGICBOARD

Main Processor: 601, 80 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 40 MHz
L1 Cache: 32K
L2 Cache: 512K
Secondary Processor: none
Slots: 4 NuBus, 1 PDS

MEMORY

Memory on Logic Board: 8 MB
Minimum RAM: 8 MB
Maximum RAM: 264 M B
RAM Slots: 8 72-pin
Minimum RAM Speed: 80 ns
RAM Sizes: 4, 8, 16, 32 MB
Install in Groups of: 2

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 7.1.2
Original Enabler: 9150 v1.0

ROM ID: \$077D
ROM Version: n/a
ROM Size: 4MB
AppleTalk Version: 58.0.2

Supported Macintosh System Software:

| | | | |
|---------------------------------------|-----------------------------------|---------------------------------------|--------------------------|
| <input type="checkbox"/> A/UX 1.0 | <input type="checkbox"/> NOS 1.11 | <input type="checkbox"/> ProDOS | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 1.11 | <input type="checkbox"/> NOS 1.3 | <input type="checkbox"/> GS/OS | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 2.0 | <input type="checkbox"/> NOS 2.0 | <input type="checkbox"/> NeXTStep 1.x | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 3.0.1 | <input type="checkbox"/> NOS 2.1 | <input type="checkbox"/> NeXTStep 2.x | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 4.1.4 | <input type="checkbox"/> LOS 7/7 | <input type="checkbox"/> NeXTStep 3.x | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 4.1.4.1 | <input type="checkbox"/> DOS 3.1 | <input type="checkbox"/> OpenStep | <input type="checkbox"/> |
| <input type="checkbox"/> A/UX 4.1.5 | <input type="checkbox"/> SOS 1.3 | <input type="checkbox"/> <1.0 | <input type="checkbox"/> |

SOUND

Built-in Microphone

Microphone Port Type: Omni
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 1, 2GB
Internal HD Interface: SCSI
Original CD-ROM Speed: 2x

HISTORY

The Workgroup Server 9150 was based on the 68040-based Workgroup Server 950. It shipped with a 80 Mhz PowerPC 601 processor and included bundled server software. It was "speed bumped" to 120 Mhz in April 1995.