

iBook SE

System Fact Sheet									
Introduced: July 1999 Discontinued: September 2000 Gestalt ID: 406 Form Factor: iBook Weight (lbs.): 6.7 Dimensions (inches): 11.6 H x 13.5 W x 1.8 D Codename: P1 Oder Number: M2453LL/A KB Article #: 60423	Max. Watts: 45 Amps: BTU Per Hour: 153.9 Voltage Range: 100-240 Freq'y Range (Hz): 50-60 Battery Type: 45 Wh Lithium Ion Soft Power Monitor Power Outlet			ADB: 0 Video: none Floppy: none SCSI: none GeoPort Connectors: none Ethernet: 10/100Base-T Microphone Port Type: none Printer Speaker Modem Headphone Airport Remote Control					
Built-in Display: 12.1-inch (diagonal) built-in TFT SVGA VRAM Speed: VRAM Needed: Video Configuration: x384 x400 x480 x870² x600 x624 x768 x870 x1024 built-in TFT SVGA active n/a n/a 32 n/a 32 n/a n/a n/a n/a n/a n/a n/a supports 640- by 480-pixel and 800- by 600-pixel resolution with millions of colors Maximum Color Bit-depth At:									
Main Processor: G3, 366 MHz PMMU: integrated FPU: integrated Data Path: 64-bit, 66/66 Mhz L1 Cache: 64K L2 Cache: 512K Secondary Processor: none Slots:	Memory on Logic Board: Minimum RAM: 64 MB Maximum RAM: 320 MB RAM Slots: 1 SO-DIM Minimum RAM Speed: 10 ns RAM Sizes: 32,64,128, 256 MB Install in Groups of: 1								
Speech R Addressing Modes: 32-bit Original SSW: 8.6 Original Enabler:	Recognition Supported ROM ROM Vers ROM S AppleTalk Vers	ID: ion: lize:	☐ A/UX ☐ A/UX ☐ A/UX ☐ A/UX ☐ A/UX ☐ A/UX	1.11 [2.0 [3.0.1 [4.1.4 [4.1.4.1 [osh Syste NOS 1 NOS 2 NOS 2 NOS 2 LOS 7 DOS 3	1.11	ware: ProDC GS/OS NeXT NeXT NeXT OpenS <a \$1799.<="" all="" and="" are="" as="" coloring="" cousins.="" dv="" for="" g4="" graphite="" href="list-style-type-st</th><th>Step 1.2
Step 2.2
Step 3.2</th><th>x 🗌</th></tr><tr><th>Microphone Port Ty Sound Sound C</th><th>STOPAGE Supports Internal CD-ROM</th><th colspan=6>Internal HD Interface: IDE</th></tr><tr><th colspan=10>Announced in February 2000, The iBook SE was a " ibook,="" ibook.="" imac="" it="" its="" of="" other="" powermac="" same="" se="" sold="" specs="" speed-bumped"="" th="" the="" with="">		