



System Fact Sheet

SYSTEM

Introduced: September 2000
Discontinued: May 2001
Gestalt ID: 406
Form Factor: iBook
Weight (lbs.): 6.7
Dimensions (inches): 11.6 H x 13.5 W x 1.8 D

Codename: Midway, P1.5
Oder Number: M6411LL/A
KB Article #: 88038

POWER

Max. Watts: 45
Amps:
BTU Per Hour: 153.9
Voltage Range: 100-240
Freq'y Range (Hz): 50-60
Battery Type: 45 Wh Lithium Ion
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 0
Video: none
Floppy: none
SCSI: none
GeoPort Connectors: none
Ethernet: 10/100Base-T
Microphone Port Type: none
 Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

1 FireWire

VIDEO

Built-in Display: 12.1-inch (diagonal) built-in TFT SVGA

		512	640	640	640	800	832	1024	1152	1280	
VRAM Speed:	VRAM Needed:	Video Configuration:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
	built-in	built-in TFT SVGA active	n/a	n/a	32	n/a	32	n/a	n/a	n/a	n/a

Maximum Color Bit-depth¹ At:

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.
supports 640- by 480-pixel and 800- by 600-pixel resolution with millions of colors

LOGICBOARD

Main Processor: G3, 366 or 466 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 66/66 Mhz
L1 Cache: 64K
L2 Cache: 512K
Secondary Processor: none
Slots:

MEMORY

Memory on Logic Board:
Minimum RAM: 32 or 64
Maximum RAM: 160 MB
RAM Slots: 1 SO-DIM
Minimum RAM Speed: 10 ns
RAM Sizes: 32,64,128, 256 MB
Install in Groups of: 1

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 9.0.4
Original Enabler:

ROM ID:
ROM Version:
ROM Size:
AppleTalk Version:

Supported Macintosh System Software:

<input type="checkbox"/> A/UX 1.0	<input type="checkbox"/> NOS 1.11	<input type="checkbox"/> ProDOS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 1.11	<input type="checkbox"/> NOS 1.3	<input type="checkbox"/> GS/OS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 2.0	<input type="checkbox"/> NOS 2.0	<input type="checkbox"/> NeXTStep 1.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 3.0.1	<input type="checkbox"/> NOS 2.1	<input type="checkbox"/> NeXTStep 2.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4	<input type="checkbox"/> LOS 7/7	<input type="checkbox"/> NeXTStep 3.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4.1	<input type="checkbox"/> DOS 3.1	<input type="checkbox"/> OpenStep	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.5	<input type="checkbox"/> SOS 1.3	<input type="checkbox"/> <1.0	<input type="checkbox"/>

SOUND

Built-in Microphone

Microphone Port Type: none
Sound In: none
Sound Out: stereo, 16-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: none
Floppy Inject: manual
Internal HD Size: 3.2 or 6 GB
Internal HD Interface: IDE
Original CD-ROM Speed: 24x

HISTORY

Announced in September 2000, the iBook (FireWire) finally brought firewire Apple's entire product line. It also introduced an innovative new combination video/audio out port (a standard miniplug), which allowed consumers to watch their iMovies (or their DVDs on the SE version) on their TV. The iBook (FireWire) was available in two configurations: a 366 Mhz model, with 64 MB of RAM cost \$1499 and was available in Indigo or Key Lime. The 466 Mhz "Special Edition" iBook came with a DVD-ROM drive, and was available in Graphite or Key Lime for \$1799.