



System Fact Sheet

SYSTEM

Introduced: January 2002
Discontinued: July 2002
Gestalt ID: 406
Form Factor: iMac Luxo
Weight (lbs.): 21.3
Dimensions (inches): 12.95 H x 15.1 W x 10.6 D
Codename: Tessera, P80
Oder Number: M8535LL/A
KB Article #:

POWER

Max. Watts: 130
Amps: 1.7
BTU Per Hour: 444.6
Voltage Range: 90-264 V
Freq'y Range (Hz): 47-63
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 0
Video: mini-VGA
Floppy: none
SCSI: none
GeoPort Connectors: none
Ethernet: 10/100Base-T
Microphone Port Type: Built-in
 Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

2 Firewire ports

VIDEO

Built-in Display: 15" (viewable) TFT active-matrix LCD

VRAM Speed:	VRAM Needed:	Video Configuration:	512	640	640	640	800	832	1024	1152	1280
n/a	DDR RAM	32 MB	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
											24

Maximum Color Bit-depth¹ At:

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

NVIDIA GeForce2 MX

LOGICBOARD

Main Processor: G4, 800 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 100 MHz
L1 Cache: 32K
L2 Cache: 256K
Secondary Processor: none
Slots: 0

MEMORY

Memory on Logic Board: none
Minimum RAM: 256 MB
Maximum RAM: 1 GB
RAM Slots: 1 SO-DIMM
Minimum RAM Speed: 100 MHz
RAM Sizes: 32, 64, 128, 256, 512 MB
Install in Groups of: 1

1 memory slot is non-user accessible and uses a 168-pin DIMM.

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 9.2
Original Enabler: n/a

ROM ID: n/a
ROM Version: n/a
ROM Size: 1 MB
AppleTalk Version: n/a

Supported Macintosh System Software:

<input type="checkbox"/> A/UX 1.0	<input type="checkbox"/> NOS 1.11	<input type="checkbox"/> ProDOS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 1.11	<input type="checkbox"/> NOS 1.3	<input type="checkbox"/> GS/OS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 2.0	<input type="checkbox"/> NOS 2.0	<input type="checkbox"/> NeXTStep 1.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 3.0.1	<input type="checkbox"/> NOS 2.1	<input type="checkbox"/> NeXTStep 2.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4	<input type="checkbox"/> LOS 7/7	<input type="checkbox"/> NeXTStep 3.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4.1	<input type="checkbox"/> DOS 3.1	<input type="checkbox"/> OpenStep	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.5	<input type="checkbox"/> SOS 1.3	<input type="checkbox"/> <1.0	<input type="checkbox"/>

SOUND

Built-in Microphone

Microphone Port Type: Built-in
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: n/a
Floppy Inject: n/a
Internal HD Size: 60 GB
Internal HD Interface: ATA
Original CD-ROM Speed: 8x4x24x

HISTORY

Apple released this revolutionary iMac on January 7 at MacWorld 2002. Brand new from the ground up, this iMac is completely unlike any of its predecessors. I have taken the liberty of adding the nickname "Luxo" after the name of the DeskLamp-character used in the Pixar logo, with whom it shares a striking resemblance.

Situated on a half-sphere base, which houses the CPU, Optical Drive, Memory and PowerSupply, the remaining portion of the iMac is a gooseneck arm and a 15" LCD display, making it the first Macintosh with varying physical dimensions depending on each individual users' ergonomic preferences.