



System Fact Sheet

"Combines the excitement of the Internet with the simplicity

SYSTEM

Introduced: April 1999
Discontinued: October 1999
Gestalt ID: 406
Form Factor: iMac Rev.D
Weight (lbs.): 40
Dimensions (inches): 15.8 H x 15.2 W x 17.6 D

Codename: Columbus, C2
Oder Number: M7441LL/A
KB Article #: 58317, 58319

Comes in five different colors: Strawberry, Blueberry, Grape, Lime and Tangerine.

POWER

Max. Watts: 80
Amps: 1.7
BTU Per Hour: 273.6
Voltage Range: 100-240
Freq'y Range (Hz): 50-60
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 0
Video: none
Floppy: none
SCSI: none
GeoPort Connectors: none
Ethernet: 10/100Base-Tx
Microphone Port Type: PlainTalk
 Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

VIDEO

Built-in Display: 15" (13.8 viewable)

Maximum Color Bit-depth¹ At:

			512	640	640	640	800	832	1024	1152	1280
VRAM Speed:	VRAM Needed:	Video Configuration:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
100MHz/10ns	SGRAM	2MB (onboard)				32	32		16		
	SGRAM	6MB				32	32		32		

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

144-pin SGRAM

NOTE: use only a SGRAM SO-DIMM. Do NOT use EDO DRAM or SDRAM-based video memory.

LOGIC BOARD

Main Processor: G3, 333 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 100 MHz
L1 Cache: 32K
L2 Cache: 512K
Secondary Processor: none
Slots: 0

MEMORY

Memory on Logic Board: none
Minimum RAM: 32 MB
Maximum RAM: 128 MB
RAM Slots: 2 SO-DIMM
Minimum RAM Speed: 10 ns
RAM Sizes: 16, 32, 64, 128 MB
Install in Groups of: 1

SOFTWARE

Speech Recognition Supported

Supported Macintosh System Software:

Addressing Modes: 32-bit
Original SSW: 8.5.1
Original Enabler:

ROM ID:
ROM Version:
ROM Size: 1 MB*
AppleTalk Version: 60

- A/UX 1.0 NOS 1.11 ProDOS
- A/UX 1.11 NOS 1.3 GS/OS
- A/UX 2.0 NOS 2.0 NeXTStep 1.x
- A/UX 3.0.1 NOS 2.1 NeXTStep 2.x
- A/UX 4.1.4 LOS 7/7 NeXTStep 3.x
- A/UX 4.1.4.1 DOS 3.1 OpenStep
- A/UX 4.1.5 SOS 1.3 <1.0

SOUND

Microphone Port Type: PlainTalk
Sound In: stereo
Sound Out: stereo

Built-in Microphone

STORAGE

Floppy Size: n/a
Floppy Inject: n/a
Internal HD Size: 6 GB
Internal HD Interface: ATA
Original CD-ROM Speed: 24x

Supports Internal CD-ROM

HISTORY

Announced in January 1999, the Rev. C iMac came in 5 dazzling new colors: Blueberry, Strawberry, Lime, Tangerine and Grape. Essentially a speed-bump of the original iMac, the Rev C. lacked both the mysterious "mezzanine" slot and the IRDA port, which lowered its price to \$1199. In April, Apple replaced the Rev. C with the Rev. D iMac, bumping the processor speed to 333 Mhz. All other specs were the same.