



System Fact Sheet

"Rip, mix, burn."

SYSTEM

Introduced: July 2001
Discontinued: January 2002
Gestalt ID: 406
Form Factor: iMac Late 2001
Weight (lbs.): 34.7
Dimensions (inches): 15 H x 15 W x 17.1 D

Codename: Kiva
Oder Number: M8492LL/A-Graphite
KB Article #: 58838

POWER

Max. Watts: 150
Amps: 1.7
BTU Per Hour: 513
Voltage Range: 100-260
Freq'y Range (Hz): 47-63
Battery Type: 3.6V lithium

Soft Power
 Monitor Power Outlet

PORTS

ADB: 0
Video: DB-15 VGA
Floppy: none
SCSI: none
GeoPort Connectors: none
Ethernet: 10/100Base-T
Microphone Port Type: Built-in

Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

2 Firewire ports

VIDEO

Built-in Display: 15" (13.8 viewable)

Maximum Color Bit-depth¹ At:

	512	640	640	640	800	832	1024	1152	1280
VRAM Speed:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
VRAM Needed:									
Video Configuration:			16 MB		32	32	32		
	n/a	SDRAM							

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

VGA port for video mirroring on all DV models

LOGIC BOARD

Main Processor: G3, 600 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 100 MHz
L1 Cache: 32K
L2 Cache: 256K
Secondary Processor: none
Slots: 0

MEMORY

Memory on Logic Board: none
Minimum RAM: 256 MB
Maximum RAM: 1 GB
RAM Slots: 2 PC100
Minimum RAM Speed: 10 ns
RAM Sizes: 32, 64, 128, 256, 512 MB
Install in Groups of: 1

SOFTWARE

Speech Recognition Supported

Supported Macintosh System Software:

Addressing Modes: 32-bit
Original SSW: 9.1
Original Enabler: n/a

ROM ID: n/a
ROM Version: n/a
ROM Size: 1 MB
AppleTalk Version: n/a

- A/UX 1.0 NOS 1.11 ProDOS
- A/UX 1.11 NOS 1.3 GS/OS
- A/UX 2.0 NOS 2.0 NeXTStep 1.x
- A/UX 3.0.1 NOS 2.1 NeXTStep 2.x
- A/UX 4.1.4 LOS 7/7 NeXTStep 3.x
- A/UX 4.1.4.1 DOS 3.1 OpenStep
- A/UX 4.1.5 SOS 1.3 <1.0

SOUND

Microphone Port Type: Built-in
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

Built-in Microphone

STORAGE

Floppy Size: n/a
Floppy Inject: n/a
Internal HD Size: 40 GB
Internal HD Interface: ATA
Original CD-ROM Speed: 8x4x24x

Supports Internal CD-ROM

HISTORY

Late in 2001, the iMac line was reduced to Indigo, Snow and Graphite. They featured a CD-RW drive, the PPC 750cx processor, which had an on-chip 1:1 L2 Cache, and a speedy new graphics chip. It featured a 600 Mhz processor, 128 MB of RAM, a 40 GB hard drive and a 56 kbps modem, the low-end was available in Indigo and Snow and was priced at \$1299.