



System Fact Sheet

SYSTEM

Introduced: July 2000
Discontinued: February 2001
Gestalt ID: 406
Form Factor: iMac Summer 2000
Weight (lbs.): 34.7
Dimensions (inches): 15 H x 15 W x 17.1 D

Codename: Perigee
Oder Number:
KB Article #: 58664

POWER

Max. Watts: 150
Amps: 1.7
BTU Per Hour: 513
Voltage Range: 100-260
Freq'y Range (Hz): 47-63
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 0
Video: DB-15 VGA
Floppy: none
SCSI: none
GeoPort Connectors: none
Ethernet: 10/100Base-T
Microphone Port Type: Built-in
 Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

2 Firewire ports

VIDEO **Built-in Display:** 15" (13.8 viewable) **Maximum Color Bit-depth¹ At:**

	512	640	640	640	800	832	1024	1152	1280
VRAM Speed:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
VRAM Needed:	n/a	SDRAM							
Video Configuration:			8 MB		32	32	32		

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.
VGA port for video mirroring on all DV models

LOGICBOARD

Main Processor: G3, 450 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 100 MHz
L1 Cache: 32K
L2 Cache: 512K
Secondary Processor: none
Slots: 0

MEMORY

Memory on Logic Board: none
Minimum RAM: 32 MB
Maximum RAM: 1 GB
RAM Slots: 2 PC100
Minimum RAM Speed: 10 ns
RAM Sizes: 32, 64, 128, 256, 512 MB
Install in Groups of: 1

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 9.0.4
Original Enabler: n/a

ROM ID: n/a
ROM Version: n/a
ROM Size: 1 MB
AppleTalk Version: n/a

Supported Macintosh System Software:

<input type="checkbox"/> A/UX 1.0	<input type="checkbox"/> NOS 1.11	<input type="checkbox"/> ProDOS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 1.11	<input type="checkbox"/> NOS 1.3	<input type="checkbox"/> GS/OS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 2.0	<input type="checkbox"/> NOS 2.0	<input type="checkbox"/> NeXTStep 1.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 3.0.1	<input type="checkbox"/> NOS 2.1	<input type="checkbox"/> NeXTStep 2.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4	<input type="checkbox"/> LOS 7/7	<input type="checkbox"/> NeXTStep 3.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4.1	<input type="checkbox"/> DOS 3.1	<input type="checkbox"/> OpenStep	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.5	<input type="checkbox"/> SOS 1.3	<input type="checkbox"/> <1.0	<input type="checkbox"/>

SOUND

Built-in Microphone

Microphone Port Type: Built-in
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: n/a
Floppy Inject: n/a
Internal HD Size: 7, 10, 20, 30
Internal HD Interface: ATA
Original CD-ROM Speed: 24x

HISTORY

Announced in July 2000, the iMac DV+ built on the success of the iMac DV. The processor speed was upped to 450 Mhz, and the hard drive was doubled to 20 GB, while the price dropped.

The iMac DV+ came with 64 MB of RAM, a 56k modem, Apple's Pro Mouse, and was available in Indigo, Ruby or Sage, all for \$1299.