



System Fact Sheet

SYSTEM

Introduced: February 2001
Discontinued: July 2001
Gestalt ID: 406
Form Factor: iMac Early 2001
Weight (lbs.): 34.7
Dimensions (inches): 15 H x 15 W x 17.1 D

Codename:
Oder Number:
KB Article #: 58791

POWER

Max. Watts: 150
Amps: 1.7
BTU Per Hour: 513
Voltage Range: 100-260
Freq'y Range (Hz): 47-63
Battery Type: 3.6V lithium
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 0
Video: DB-15 VGA
Floppy: none
SCSI: none
GeoPort Connectors: none
Ethernet: 10/100Base-T
Microphone Port Type: Built-in
 Printer **Speaker**
 Modem **Headphone**
 Airport **Remote Control**

2 Firewire ports

VIDEO

Built-in Display: 15" (13.8 viewable)

		<i>Maximum Color Bit-depth¹ At:</i>								
		512	640	640	640	800	832	1024	1152	1280
VRAM Speed:	VRAM Needed:	x384	x400	x480	x870 ²	x600	x624	x768	x870	x1024
n/a	SDRAM				32		32		32	
Video Configuration:		8 MB								

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.
 VGA port for video mirroring on all DV models

LOGICBOARD

Main Processor: G3, 600 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 100 MHz
L1 Cache: 32K
L2 Cache: 256K
Secondary Processor: none
Slots: 0

MEMORY

Memory on Logic Board: none
Minimum RAM: 32 MB
Maximum RAM: 1 GB
RAM Slots: 2 PC100
Minimum RAM Speed: 100 MHz
RAM Sizes: 32, 64, 128, 256, 512 MB
Install in Groups of: 1

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 9.1
Original Enabler: n/a

ROM ID: n/a
ROM Version: n/a
ROM Size: 1 MB
AppleTalk Version: n/a

Supported Macintosh System Software:

<input type="checkbox"/> A/UX 1.0	<input type="checkbox"/> NOS 1.11	<input type="checkbox"/> ProDOS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 1.11	<input type="checkbox"/> NOS 1.3	<input type="checkbox"/> GS/OS	<input type="checkbox"/>
<input type="checkbox"/> A/UX 2.0	<input type="checkbox"/> NOS 2.0	<input type="checkbox"/> NeXTStep 1.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 3.0.1	<input type="checkbox"/> NOS 2.1	<input type="checkbox"/> NeXTStep 2.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4	<input type="checkbox"/> LOS 7/7	<input type="checkbox"/> NeXTStep 3.x	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.4.1	<input type="checkbox"/> DOS 3.1	<input type="checkbox"/> OpenStep	<input type="checkbox"/>
<input type="checkbox"/> A/UX 4.1.5	<input type="checkbox"/> SOS 1.3	<input type="checkbox"/> <1.0	<input type="checkbox"/>

SOUND

Built-in Microphone

Microphone Port Type: Built-in
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: n/a
Floppy Inject: n/a
Internal HD Size: 7, 10, 20, 30
Internal HD Interface: ATA
Original CD-ROM Speed:

HISTORY

Announced in February 2001, the iMac SE brought a number of small improvements over the previous high-end iMac, in addition to a dramatic change in the iMac "colors". Apple chose to get rid of Sage and Ruby in favor of "Blue Dalmatian" and "Flower Power", two new patterns that were molded into the case using a technique which took Apple 18 months to perfect.

The iMac SE featured a CD-RW drive, a new and improved PPC 750cx processor, which had an on-chip 1:1 L2 Cache, and a speedy new graphics chip. It featured a 600 Mhz processor, 128 MB of RAM, a 40 GB hard drive and a 56 kbps modem, was available in Graphite, Blue Dalmatian or Flower Power, and was priced at \$1499.