

iMac/iMac DV (Slot Loading CD-ROM)

System Fact Sheet

0	COULD A
-	SIHVI

Introduced: October 1999 **Discontinued:** July 2000 Gestalt ID: 406 Form Factor: iMac Slot Load

Weight (lbs.): 34.7

Dimensions (inches): 15 H x 15 W x 17.1 D

Codename: Kihei Oder Number: **KB Article #:** 58474

Comes in five different colors: Strawberry, Blueberry, Grape, Lime and Tangerine.

POWER

Max. Watts: 80 **Amps:** 1.7 BTU Per Hour: 273.6 Voltage Range: 100-240 Freq'y Range (Hz): 50-60

> Battery Type: 3.6V lithium **⊠** Soft Power

> > **☐** Monitor Power Outlet

PORIS

ADB: 0

Video: DB-15 VGA

Floppy: none SCSI: none

GeoPort Connectors: none

☐ Airport

Ethernet: 10/100Base-T

Microphone Port Type: PlainTalk

☐ Printer **⊠** Speaker

Modem **Headphone**

Video port is on DV models only and supports video mirroring only. FiareWire available on DV and Special Edition models.

VDEO

Built-in Display: 15" (13.8 viewable)

VRAM Speed: VRAM Needed:

Video Configuration:

640 512 x384 x400

640 640 $x480 \quad x870^{2}$

☐ Remote Control

800 832 1024 1152 1280 x600 x624 x768 x870 x1024

Maximum Color Bit-depth¹ At:

100MHz/10ns SGRAM 8MB 32 32 16

VGA port for video mirroring on all DV models

LOGOBOARD

Main Processor: G3, 350 or 400 MHz

PMMU: integrated FPU: integrated Data Path: 64-bit, 100 MHz

L1 Cache: 32K L2 Cache: 512K Secondary Processor: none Slots: 0

MEVORY

Memory on Logic Board: none Minimum RAM: 64 MB Maximum RAM: 512 MB RAM Slots: 2 PC100

Minimum RAM Speed:

RAM Sizes: 64, 128, 256 MB

Install in Groups of: 1

SOFIWARE

Addressing Modes: 32-bit Original SSW: 8.6

Original Enabler:

☐ Speech Recognition Supported

ROM ID: **ROM Version:** ROM Size: 1 MB*

AppleTalk Version: 60

Sup	por	ted	Mac	cintos	h S	ys	tem	Soi	twar	e:

☐ ProDOS ☐ A/UX 1.0 NOS 1.11 A/UX 1.11 GS/OS NOS 1.3 NeXTStep 1.x A/UX 2.0 ☐ NOS 2.0 NeXTStep 2.x A/UX 3.0.1 □ NOS 2.1 A/UX 4.1.4 LOS 7/7 NeXTStep 3.x A/UX 4.1.4.1 OpenStep

☐ A/UX 4.1.5

DOS 3.1 ☐ SOS 1.3

SUND

⊠ Built-in Microphone

Microphone Port Type: PlainTalk Sound In: stereo

Sound Out: stereo

STORAGE

Supports **⊠** Internal CD-ROM

Floppy Size: n/a Floppy Inject: n/a Internal HD Size: 6, 10, 13 GB **Internal HD Interface: ATA** Original CD-ROM Speed: 24x

<1.0

HSTORY

Announced in October 1999, The iMac (Slot Loading) was the low end of a new "good, better, best" iMac product staregy from Apple. The iMac SL built on the success of the rev. D iMacs, adding a faster processor, more RAM (64 MB base), a better graphics sub-system, an improved speaker system, and a slot-loading CD-ROM drive. With all these new features, the iMac SL was still \$200 cheaper than predecessor. At \$999, the blueberry-only iMac SL was the cheapest Apple-branded machine in many years.

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.