
Apple 3.5 Drive



Overview

Small in size but large in power, the Apple[®] 3.5 Drive stores 800K of data on a single 3.5-inch disk. It's a flexible, economical choice for owners of Macintosh[™] Plus, Macintosh SE, and Apple IIGs[™] personal computers who want high-capacity storage at an affordable price.

Features

Benefits

 Uses 800K double-sided, 3.5-inch floppy disks 	 Provides over 2.5 times the capacity of on-line data storage available from 5.25-inch disks. Lets you hold large data files and applications on one disk, reducing the need to swap disks. Retrieves and stores data substantially faster than a 5.25-inch drive. Provides compatibility with 400K disks. Protects data, because disks are rugged and easy to carry. Allows Apple IIGs owners to run applications that come on 3.5-inch disks.
 Easy Apple II system expandability 	► Lets you add up to three additional disk drives (either 3.5-inch or 5.25 inch) to increase storage capacity as your needs change.
► In-use light	Indicates when drive is running.



Apple 3.5 Drive

System Requirements	To use the Apple 3.5 Drive, you will need one of the following:	 A Macintosh Plus A Macintosh SE A Macintosh 512K Enhanced 	An Apple IIGS
Technical Specifications	 Recording media Disk diameter: 3.5 inches Recording surfaces: 2 Tracks per inch: 80 Capacity Formatted data capacity: 800 kilobytes* Unformatted data capacity: 1,246 kilobytes Disks used in the Apple 35 Drive should contain certified double-sided media Drive characteristics Seek time (track to track): 6 milliseconds maximum Settle time: 30 milliseconds maximum Drive startup time: 600 milliseconds maximum 	Head position accuracy ▶ ±0.035 mm Interfaces ▶ Connects directly to the disk-drive port of the Macintosh 512K Enhanced, Macintosh Plus, Macintosh SE, or Apple IIGS. With the Apple IIGS, an addi- tional drive can be daisy- chained to the first drive. Electrical requirements ▶ + 12 volts —Standby: 10 microamps —Typical: 120 milliamps (during eject only: 2-second maximum duration) ▶ +5 volts —Standby: 10 milliamps —Typical: 360 milliamps	 Environmental requirements Deperating temperature: 40° to 122° F (5° to 50° C) Storage temperature: -40° to 140° F (-40° to 60° C) with no condensation Relative humidity: 5% to 90% (with maximum wet bulb temperature of 85° F [29°C] and no condensation) Size and weight Height: 2.01 in. (51 mm) Width: 4.72 in. (120 mm) Depth: 7.87 in. (200 mm) Weight: 2.8 lb. (1.3 kg)
Ordering Information	Apple 3.5 Drive	Order No. A9M0106	With your order, you'll receive: Apple 3.5 Drive

Owner's guide

Limited warranty statement

Apple Computer, Inc.

20525 Mariani Avenue Cupertino, CA 95014 (408) 996-1010 TLX: 171-576

© 1987 Apple Computer, Inc. Apple and the Apple logo are registered trademarks of Apple Computer, Inc. Apple IIcs, Macintosh are trademarks of Apple Computer, Inc. July 1987. Product specifications are subject to change without notice. M2236